	WATER W	ELL RECORD	Form WV	VC-5	KSA 82a			-
OCATION OF WATER WELL:	Fraction				Number	Township Nu		Range Number
unter Fallage ads		V N 14	540 14		<u> </u>	T 26	S	R /9 (EW)
stance and direction from nearest town or city street address of well if located within city?								
6345 1W	KINSI.	c4 5	<u>ans</u>	9.5				
WATER WELL OWNER: Lew	is BAO	5.						
#, St. Address, Box # :		・ ' ' ' ' ' ' '				Board of A	griculture,	Division of Water Resources
y, State, ZIP Code :	15/11/5/	ey no	175			Application	Number:	
COATE WELL'S LOCATION WITH	DEPTH OF COMP	PLETED WELL.	6.0) f	t. ELEVA	TION:		
AN "X" IN SECTION BOX:	enth(s) Groundwate	er Éncountered	1 <i>A</i>	. X	ft. 2	2	ft. 3	3 <u> </u>
	VELL'S STATIC WA	TER LEVEL	.⋧.≱	ft. belov	y Jand sur	face measured on	mo/day/yr	\sim
	Pump tes	st data: Well w	ater was .	.2.8	ft. a	fter	hours pu	umping 、 。 う gpm
NW NE	st Yield 20	gpm: Well w	ater was _		ft. a	fter	hours pu	ımping gpm
	ore Hole Diameter.	\$ 3/4cin.	to	, <u>C</u>	ft., a	and	in	ı. to
	VELL WATER TO B	ľ	5 Public		ylogu	8 Air conditioning	11	Injection well
	1)Domestic	3 Feedlot				9 Dewatering		Other (Specify below)
SW SE	2 Irrigation	4 Industrial				10 Observation we		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
								, mo/day/yr sample was sub-
	nitted	onological camp				ter Well Disinfecte		
TYPE OF BLANK CASING USED:		Wrought iron	8 C	oncrete	tile	CASING JO	NTS: Glue	d .XClamped
1 Steel 3 RMP (SR)		Asbestos-Ceme	nt 9 C	ther (sp	ecify belov	w)	Weld	ded
2 PVC 4 ABS		Fiberglass		• •	•	·	Thre	aded
ink casing diameter in	10 40°	ft Dia						in. to <u></u> ft.
sing height above land surface	/2 in	weight			lbs./	ft. Wall thickness	or gauge N	10. JDR-26
PE OF SCREEN OR PERFORATION		woight		7 PVC			estos-cem	
1 Steel 3 Stainless		Fiberglass		B RMP (SR))
2 Brass 4 Galvanize		Concrete tile	<u> </u>	9 ABS	J,		ne used (o	
REEN OR PERFORATION OPENING			auzed wrapp	_	(8 Saw cut		11 None (open hole)
1 Continuous slot 3 Mill			ire wrapped		·	9 Drilled holes		,
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
From								
GRAVEL PACK INTERVALS: From. 25 ft. to 60 ft., From ft. to								
GRAVEE PACK INTERVACE.	From	ft. to			ft., Fro		ft.	
GROUT MATERIAL: 1 Neat ce		Cement grout		Bentonite				
						•		ft. to ft.
at is the nearest source of possible c		,				stock pens		Abandoned water well
1 Septic tank 4 Lateral		7 Pit privy			11 Fuel	storage	15 (Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon						lizer storage		Other (specify below)
3 Watertight sewer lines 6 Seepa		, 9. Feedyard				cticide storage		stuse
rection from well?	Ca	11/0	-			iny feet?		
ROM TO	LITHOLOGIC LO		FRO	ЭМ	то		LITHOLO	GIC LOG
0 2 Top.	5011							
2 21 Sand	n Clay		· ·					
21 26 BROW	20/04						Man Mark Marketing	
26 8 GRA	,le				R			
	1							
						JUL 0 9 198	5	
					D 1105	05 011 5		
					BURE	au of oil f	IELD &	
					ENVIR	ONMENTAL G	EOLOGY	
								4
	~ · · · · · · · · · · · · · · · · · · ·							
						<u> </u>		
			1			anothered or (3)	nlugged ur	oder my judediction and was
CONTRACTOR'S OR LANDOWNER	S CERTIFICATION	i: This water we	Was (1) 9	onstructe	(C, (2) 190	onstructed, or (3)	plugged ui	nowledge and belief Kansas
mpleted on (mo/day/year)								nowledge and belief. Kansas
ater Well Contractor's License No. This Water Well Record was completed on (me/day/yr)								
der the business name of a 1	tayes 10 a	DESC FIRM		Clearly	Dy (Signa Please fili	in blanke underline		
STRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top ree copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL								
WNER and retain one for your records	3.	.,						