

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Edwards		SE 1/4 SE 1/4 NW 1/4		8		T 26 S		R 19 EW	
Distance and direction from nearest town or city street address of well if located within city? 6 1/2 South of Kinsley, Kansas									
2 WATER WELL OWNER: Lewis Brothers RR#, St. Address, Box # : Kinsley, Kansas City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:						
			Depth(s) Groundwater Encountered 1. 32 ft. 2. 32 ft. 3. 32 ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 4/27/87 Pump test data: Well water was 32 ft. after 1 hours pumping 3 gpm Est. Yield 15 gpm: Well water was 32 ft. after 1 hours pumping 3 gpm Bore Hole Diameter 8 3/4 in. to 50 ft., and 50 ft. to 50 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well X Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No..... XX ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped..... X PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded..... Blank casing diameter 6 in. to 40 ft., Dia. 40 in. to 40 ft., Dia. 40 in. to 40 ft. Casing height above land surface 24 in., weight SDR21 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: X PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped X Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 40 ft. to 50 ft., From 40 ft. to 50 ft., From 40 ft. to 50 ft. GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From 20 ft. to 50 ft., From 20 ft. to 50 ft.									
6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Cattle Direction from well? Pasture How many feet? FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 3 Top soil 3 30 Sand 30 40 White clay 40 50 Gravel									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/27/87 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 224 This Water Well Record was completed on (mo/day/yr) 6/17/87 under the business name of Carl Hayse Water Well Service by (signature) Carl Hayse INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.									