USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department af Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County Edwards	Fraction Centerof		Section number		Township number Range number			
2 Distance and die.		1/4 Gen /4 N	<del></del>	ner of well	, T	T S S S S S S S S S S S S S S S S S S	R -/	_E(W_)	
2. Distance and direction from nearest town or city:  745 44 from Kinsley  Street address of well location if in city:				ner of well r street:	•	Kinsley, KS 67547			
				tate, zip	code: I				
4. Locate with "X" i				6. Bore hole dia. 28 in. Completion date  Well depth 110 ft. 4-17-77  7 Cable tool Rotary Driven Dug					
•									
136/				Hollow rad Jetted Bored X_ Reverse rotary					
'				8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock					
- "	E						r conditioning Stoc I field water Othe		
SW	SE					9. Casing: Material <u>Stee</u>	Height: Above or bel		
<u>!                                    </u>						Threoded Welded _X		in.	
1 M						Dia. 16 in. to 0 ft. dept	h Wall Thickness: inch	es or	
5. Type and color of material				From	То	Dia. 16in. to 0 ft. depth Wall Thickness; inches or Dia. 16in. to 50ft. depth gage No. 188			
Surface				0	2	W. A. Brown			
				<del></del>	7.0		ridge Dia. 16 Length 60		
Sand				2	10	Set between50	ft. andft.		
Clay				10	15	Gravel pack? X Size ran	range of material 1/4 to 5		
Sand & Gravel				15	35	11. Static water level;	. Static water level: mo./day/yr.		
				+		ft. below land surf		<del>-77</del>	
Clay				35	37		2. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.		
Sand & Gravel				37	103	l no test			
Clay & Sand Streaks				103	108	Estimated maximum yield 110 000 g.p.m.  13. Water sample submitted: mo./day/yr.			
Caliche & Clay				100	100		)ate		
				108	120	14. Well head completion: Pitless adapter	12 Inches above gr	ode	
						15. Well grouted? X			
						With: Neat cement X Depth: From 0 ft. to	Bentonite Co 10 ft	ncrete -	
						16. Negrest source of possible ft. IMILE Direction			
						Well disinfected upon completed 17. Pump:	tion?Yes Not installed	— <sup>№</sup>	
						Manufacturer's nameSi	mmons	<sup>"</sup>	
						Model number 4-5-110  Length of drop pipe 100	0 HP <u>80</u> Volts _ ft. capacity 1 000 <sub>g</sub>	.p.m.	
						Туре:			
						Submersible Jet	X Turbine Reciproce		
(Use a second sheet if needed)					L	Centrifugal Other			
18. Elevation:	19. Remarks:					20. Water well contractor's con		eport	
(22)						is true to the best of my knowl	edge and belief.	. ]	
Topography:						Woofter Drillin		13 se No.	
Slope			•			Address Hwy 46		S	
A Upland Valley						Signed Authorized repr	esentative	2/6/p	