COUNTY:	024 EDWA	RDS : NE	tion 1/4 NE 1/4 SE	; Sec 1/4 ; 34	:Tion Numbe 	r ; ; 	T 26	Number S	; Ra ; R	
11 1/2 S		KINSLEY, KS	town or city street							
WATER WE	LL OWNER:	VERNON D								Resources
City, St			KS 67547-		Applica	tion Num				
LOCATE #			; 4 DEPTH OF COMPL ; Depth(s) Groun		ELEV	ATION:				
			WELL'S STATIC WA	ATER LEVEL 50 testdata: Well					n mo/day ours pum	*
·	1		Estimated Yield	gpm: Well	water was	f	t. after	h	ours pum	ping g
	! ! !		E ¦ Bore Hole Diamet	ter 8.75	in. to	130 ft.,	and	in. t	0	ft.
1	; S₩	! SE!	WELL WATER TO BE	E USED AS: 01 D O	MESTIC					
, !	i i			bacteriological	sample sub	mitted to	o departa			
TYPE OF Blank ca Casing h TYPE OF	¦ BLANK CAS sing diam eight abo SCREEN OR	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER.	; If yes, mo/day/y ; CASIN to 120 ft., Dia 12 in., weight	yr sample was su NG JOINTS: SLUED a in. to	ft.,	Dia	in. te	- -		sinfected? Y
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER. TION OPENINGS ARE: INTERVALS:	; If yes, mo/day/y ; CASIN to 120 ft., Dia 12 in., weight	yr sample was su NG JOINTS: GLUED in. to t lbs/ft.	ft., Wall thic	Dia kness or	in. to gauge No	. 26	 ft.	
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED	ING USED: O2 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE:	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to	yr sample was su NG JOINTS: GLUED a in. to t lbs/ft. 130 ft., Fro t 130 ft., Fro	ft., Wall thic	Dia kness or . to . to	in. to gauge No	. 26	 ft.	
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GR GROUT MA' Grout In What is	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: 03 BENTONITE From tto	CASIM to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT From 120 ft. to From ft. to From ft. to	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or . to . to . to	in. to gauge No ft. ft. ft.	. 26	ft.	
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GR GROUT MA' Grout In What is	BLANK CAS sing diam eight abo SCREEN OR PERFORATED AVEL PACK TERIAL tervals: the neare of from we	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: O3 BENTONITE From ft. to st source of possib	CASIM to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAW CUT From 120 ft. to From ft. to From ft. to From ft. to	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or . to . to . to	in. to gauge No ft. ft. ft. ft.	5. 26	ft.	ny feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GROUT MA' Grout In What is Direction FROM :	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare of from we 15 24	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: O3 BENTONITE From ft. to st source of possil 11? ALL SILT & SAND GREY CLAY	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to From ft. to From ft. to 25 ft., From ble contamination: C	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or to to to	in. to gauge No ft. ft. ft. ft.	5. 26	ft. How ma	ny feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GROUT MA' Grout In What is Direction FROM : 15 ; 24 ;	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK FERIAL tervals: the neare of from we 15 24 69	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: 03 BENTONITE From ft. to st source of possib 11? ALL SILT & SAND GREY CLAY 05 SAND AND 17 E	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to From ft. to From ft. to 25 ft., From ble contamination: C	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or to to to	in. to gauge No ft. ft. ft. ft.	5. 26	ft. How ma	ny feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GROUT MA' Grout In What is Direction FROM :	BLANK CAS sing diam eight abo SCREEN OR R PERFORA ERFORATED AVEL PACK TERIAL tervals: the neare of from we 15 24	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: O3 BENTONITE From ft. to st source of possil 11? ALL SILT & SAND GREY CLAY	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to From ft. to From ft. to 25 ft., From ble contamination: C ITHOLOGIC LOG	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or to to to	in. to gauge No ft. ft. ft. ft.	5. 26	ft. How ma	ny feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GROUT MA Grout In What is Direction FROM : 15 : 24 ; 69 :	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK FERIAL tervals: the neare 1 from we 15 24 69 121	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: O3 BENTONITE From	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to From ft. to From ft. to 25 ft., From ble contamination: C ITHOLOGIC LOG	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or to to to	in. to gauge No ft. ft. ft. ft.	5. 26	ft. How ma	ny feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O SCREEN P GROUT MA Grout In What is Direction FROM : 15 : 24 ; 69 :	BLANK CAS sing diam eight abo SCREEN OR R PERFORATED AVEL PACK FERIAL tervals: the neare 1 from we 15 24 69 121	ING USED: 02 PVC eter 5 in ve land surface PERFORATION MATER: TION OPENINGS ARE: INTERVALS: INTERVALS: O3 BENTONITE From	CASIN to 120 ft., Dia 12 in., weight IAL: 07 PVC 08 SAN CUT From 120 ft. to From ft. to From ft. to 25 ft., From ble contamination: C ITHOLOGIC LOG	yr sample was su NG JOINTS: GLUED in. to lbs/ft. 130 ft., Fro 130 ft., Fro ft., Fro	ft., Wall thic	Dia kness or to to to	in. to gauge No ft. ft. ft. ft.	5. 26	ft. How ma	ny feet?

Water Well Contractor's License No. 224 This Water Well Record was completed on /mo/day/yr) /12/18/93

by (signature)

under the business name of CARL HAYSE WATER WELL SVC