		10 G (New) LL RECORD	Form W	WC-5	D:		D A N	25815	
		OF WATER WELL:	Fraction	W C-3		vision of wate on Number	r Resources App. No.	Range Number	
Coun		Edwards	1/4 NE 1/4 SW	/ 1/4 NE 1/4		35		R 19 ☐E ⊠W	
Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here					Latitu	Latitude: 37.744107 (in decimal degrees)			
Approximately 10 miles north and 4 miles west of Greensburg.					Long	Longitude: -99.363941 (in decimal degrees)			
,,						ition:		(
2 WATER WELL OWNER: Roger Stotts					→ Datun	n: 🔲 WGS 8	4, 🛛 NAD 83, 🔲	NAD 27	
RR#, Street Address, Box #: 22259 Hwy 183					— Collect	Collection Method: ☑ GPS unit (Make/Model: WAAS)			
City, State, ZIP Code : Greensburg, KS 67054						☐ GPS unit (Make/Model: VVAAS Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, Saite, 211 Code . Grootispurg, NO 07004						ccuracy:	$3 \text{ m}, \boxtimes 3-5 \text{ m}, \square$	5-15 m. >15 m	
3 LOCATE WELL									
WITH AN "X" IN SECTION BOY: ft.									
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL 64.80 ft. below land surface measured on mo/day/yr 12/08/11									
WELL'S STATIC WATER LEVEL 51.00 ft, below land surface measured on mo/day/yr 12/00/11									
Pump test data: Well water was Not checked ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm									
1	W I ESI. YIELD gpm. Well water was it. after hours pumping gpm Bore Hole Diameter 24 in. to 174 ft., and in. to ft.								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well									
Domostic Cooler Coil field water gumbly Devetoring Cother (Specify Islam)									
SWSE Domestic Feeding Off field water supply Dewatering Officer (Specify below) Irrigation									
Was a chemical/bacteriological sample submitted to Department? Yes X No									
If yes, mo/day/yr sample was submitted									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: X Glued Clamped Welded Threaded									
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter 16 in. to 133 ft., Diameter 16 in. to 158 ft., Diameter in. to ft. Casing height above land surface 12 in., Weight 19.75 lbs./ft., Wall thickness or gauge No616									
Casing height above land surface 12 in., Weight 19.75 lbs./ft., Wall thickness or gauge No616									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:									
Continuous slot Mill slot Gauze wrapped Torch cut Dirilled holes None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From 133 ft. to 149 ft., From ft. to ft.									
Fromft. toft., From ft. toft.									
	GRAV	EL PACK INTERVALS:	From 23	ft. to	174	ft., From _	ft. 1	to ft.	
(070			From	ft. to		ft., From _	ft. t	<u> </u>	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 3 ft. to 23 ft., From ft. to ft.									
What is	the near	est source of possible contra	mination:		11. 10	II.,	, rrom	II. 10	
What is	Septic ta			Livestock	nens	Insecticide	storage X Oth	er (specify below)	
	Sewer lin	nes Cesspool	Sewage lagoon	Fuel stora			l water well	· · · · /	
		ht sewer lines Seepage 1	oit Feedyard [Fertilizer s	-	Oil well/ga	as well	None Known	
	ction from			Distance					
FROM	TO	LITHOLOG	HC LOG	FROM	ТО		OG (cont.) <u>or</u> PLU	GGING INTERVALS	
3	3	Topsoil	off	400	400	fine	ا د ا داخان من		
18	18 23	Clay, brown, sandy, s		129 133	133		wn, white, hard	olov brown 9 white	
23	36	Sand, coarse to fine, Clay, brown, hard	ioose, ciean	133	136 149			clay, brown & white	
36	84	Sand, coarse to fine,	with gravel coarse	130	148	medium,	arse to fine, with	graver, coarse,	
- 30		to fine, clay streak at		149	158			, cement sand streak	
84	93	Clay, white, brown, h		170	100	at 154'	vvii a vviille, fialu	, Johnson Sand Streak	
31		streaks	a. a, mai giavoi	158	170		arse to fine with	gravel, medium to	
93	116	Clay, brown, white, h	ard			fine		g. a. a., modium to	
116	129	Sand, coarse to fine,		170	174		wn & white, hard		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) _ 12/08/11 _ and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 12/09/11									
under the business name of Clarke Well & Equipment, Inc. by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.									
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									