

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick NW NE NE SE E W Distance and direction from nearest town or city street address of well if located within city limits: 140 South 2nd Colwich, KS		NW ¼ NE ¼ NE ¼ SE ¼	21	T 24 S R 2 E W	
2) WATER WELL OWNER: Agnes Landwehr					
RR#, St. Address, Box #: 2436 Morning Dew		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: Wichita, KS 67205		Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 52 ft.			
A 2x2 grid representing a quarter-section. The top-left square is labeled 'NW', top-right 'NE', bottom-left 'SW', and bottom-right 'SE'. An 'X' is drawn in the center of the 'NE' square. To the left of the grid is a vertical scale bar labeled '1 Mile'.		ELEVATION:			
		Depth(s) Groundwater Encountered: 10 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr 8-22-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter: in. to ft., and in. to ft.					
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well ☒ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes..... No ☒		If yes, mo/day/yr sample was submitted			
5) TYPE OF BLANK CASING USED:		CASING JOINTS:			
1 Steel ☒ 2 PVC 3 RMP (SR) 4 ABS		5 Wrought iron 8 Concrete tile Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
Blank casing diameter: 2 in. Dia in. to ft., Dia in. to ft.					
Casing height above land surface: 2 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From ft. to ft., From ft. to ft.			
6) GROUT MATERIAL:		1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other Grout Intervals: From 52 ft. to ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ☒ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? East How many feet? 4			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			52	0	concrete
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 8-22-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on 8-24-95 under the business name of Weninger Drilling by (signature) Karina Mourner					