

MW # 9

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>SEDGWICK</u>	<u>NW 1/4 NW 1/4 SW 1/4</u>	<u>1</u>	T <u>26</u> S	R <u>2</u> EW

Distance and direction from nearest town or city street address of well if located within city?

7400 N. 135 St West Maize, KS

2 WATER WELL OWNER: <u>CHASE PIPES LINE</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>Rural Rt #1 Box 173</u>	Application Number:
City, State, ZIP Code: <u>El Dorado, KS 67042</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>14</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>5'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter <u>7 1/4</u> in. to <u>14</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
<u>6</u> PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>2</u> in. to <u>4</u> ft., Dia.			
Casing height above land surface <u>30"</u> in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>0</u> PVC	10 Asbestos-cement	
1 Steel	8 RMP (SR)	11 Other (specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless steel			
4 Galvanized steel			
5 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
<u>3</u> Mill slot <u>0.10</u>	7 Torch cut	10 Other (specify)	
2 Louvered shutter			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From <u>14</u> ft. to <u>4</u> ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From <u>14</u> ft. to <u>3.5</u> ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	<u>0</u> Cement grout	<u>0</u> Bentonite	4 Other
GROUT INTERVALS:	From <u>2.0</u> ft. to <u>SURFACE</u> ft.	From <u>3.5</u> ft. to <u>2.0</u> ft.	From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	<u>11</u> Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>North</u>			How many feet? <u>260'</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>3</u>	<u>DARK BROWN SILTY CLAY</u>			
<u>3</u>	<u>4</u>	<u>SILTY SAND TRACES OF CLAY</u>			
<u>4</u>	<u>5.5</u>	<u>VERY FINE SAND & SOME SILT</u>			
		<u>WET</u>			
<u>5.5</u>	<u>14'</u>	<u>MEDIUM TO COARSE SAND</u>			
		<u>SATURATED VERY COARSE</u>			
		<u>SAND & SORTED GRAVEL</u>			
		<u>FROM 9' - 14'</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>1</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-11-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>10-6-95</u> under the business name of <u>KURTZ ENVIRONMENTAL SERVICE</u> by (signature) <u>[Signature]</u>
