

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>NW 1/4 NE 1/4</u>		Section Number: <u>21</u>		Township Number: <u>T 26 S</u>		Range Number: <u>R 2 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>445 S 4th Colwich</u>									
2 WATER WELL OWNER: <u>Jon & Rhonda Niles</u> RR#, St. Address, Box #: <u>2402 W 21st N</u> City, State, ZIP Code: <u>Goodland KS 67052</u>					Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: <u>66</u> ft. ELEVATION: <u>8-10-96</u> ft.						
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL 1. ft. below land surface measured on mo/day/yr						
			Pump test data: Well water was ft. after hours pumping gpm						
			Est. Yield 10 gpm Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 11 in. to 66 ft., and in. to ft.						
			WELL WATER TO BE USED AS:						
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
			Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted						
			Water Well Disinfected? Yes <u>X</u> No						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded									
Blank casing diameter in. to 56 ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160 FSC									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 56 ft. to 66 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 1 ft. to 66 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 3 ft. to 1 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage									
Direction from well? <u>West</u> How many feet? <u>50</u>									
FROM TO LITHOLOGIC LOG					FROM TO PLUGGING INTERVALS				
0 2 top soil									
2 26 shale									
26 50 clay									
50 66 light to medium sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-10-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>86</u> This Water Well Record was completed on (mo/day/yr) <u>8-10-96</u> under the business name of <u>Wenger Drilling Inc</u> by (signature) <u>Michelle Becker</u>									