

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 NW 1/4 Section Number 27 Township Number T 26 S 6 Range Number R 2 E W

County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? 16545 W. 45th N. Colwich

2 WATER WELL OWNER: Tim Dold RR#, St. Address, Box #: PO Box 336 City, State, ZIP Code: Colwich, KS 67030 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NW corner]

4 DEPTH OF COMPLETED WELL: 91 ft. ELEVATION: 5-29.97 ft. below land surface measured on mo/day/yr

WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 gpm: Well water was 11 in. to 91 ft. and 12 Other (Specify below)

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded

Blank casing diameter 5 in. to 79 ft. Dia 2.40 in. to 160 RSE lbs./ft. Wall thickness or gauge No. 160 RSE

Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 RSE

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 79 ft. to 91 ft. From 28 ft. to 91 ft.

GRAVEL PACK INTERVALS: From 28 ft. to 91 ft.

6 GROUT MATERIAL: 3 Neat cement 28 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 28 ft. From 3 ft. to 28 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? Southwest How many feet? 160 ft.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-29-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 38 This Water Well Record was completed on (mo/day/yr) 5-29-97 under the business name of Weneringer Drilling Inc. by (signature) Michelle Becker

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.