

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 NE 1/4 SW 1/4		Section Number 25	Township Number T 26 S	Range Number R 2W E4V
Distance and direction from nearest town or city street address of well if located within city? 135th West, 1/2 m. N. of 37th, 1/4 E. (NW Sewer Plant) Wichita, KS.						
WATER WELL OWNER: WICHITA, CITY OF		Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 455 N. Main		Application Number: 20000247				
CITY, STATE, ZIP CODE: Wichita, Kansas 67202						
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 65 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 14 FT. BELOW LAND SURFACE MEASURED ON 03/06/2001 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 12 in. to 65 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF CASING USED:		CASING JOINTS:				
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (Specify below) 7 Fiberglass SDR-26				
Blank casing Diameter 8 in. to 20 ft., Dia in. to ft., Dia in. to ft.		Wall thickness or gauge No. .332				
Casing height above land surface 12 in., weight 5.52 lbs. / ft.						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 8 RMP (SR) 10 Asbestos-cement 11 other (specify) 12 None used (open hole)				
1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel		5 Fiberglass 6 Concrete tile 8 Saw cut 11 None (open hole)				
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 9 Drilled holes 10 Other (specify)				
1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched						
SCREEN-PERFORATION INTERVALS:		from 20 ft. to 60 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 65 ft., From ft. to ft. from ft. to ft., From ft. to ft.				
6 GROUT MATERIAL:		4 Other bentonite hole plug				
1 Neat cement 2 Cement grout 3 Bentonite Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.		10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent				
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	4	topsoil				
4	15	clay				
15	25	fine sand				
25	32	coarse sand				
32	38	clay				
38	55	medium sand				
55	65	coarse sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/06/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 03/09/01 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp						