

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 16 Township Number 26 S Range Number 2 EW County Sedgwick Distance and direction from nearest town or city street address of well if located within city? 1609 Brookside Ct.

2 WATER WELL OWNER: Brian Kraus RR#, St. Address, Box #: P.O. Box 471 City, State, ZIP Code: Colwich, KS 67030 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section (16).] 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 3101 ft. Depth(s) Groundwater Encountered: 12 ft. below land surface measured on mo/day/yr 3101 ft. WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr 3101 ft. Pump test data: Well water was 11 in. to 65 ft. after 11 hours pumping 25 gpm. Est. Yield 25 gpm. Well water was 11 in. to 65 ft. after 11 hours pumping 25 gpm. Bore Hole Diameter: 11 in. to 65 ft. and 11 in. to 65 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 53 in. Dia 2.40 in. to 160 psi ft. Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut 65 SCREEN-PERFORATED INTERVALS: From 53 ft. to 65 ft. From 12 ft. to 65 ft. GRAVEL PACK INTERVALS: From 12 ft. to 65 ft. From 12 ft. to 65 ft.

6 GROUT MATERIAL: 3 1 Neat cement 12 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 12 ft. From 12 ft. to 65 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? east How many feet? 12

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-10-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 3-22-01 under the business name of Weninger Drilling Inc. by (signature) Michelle Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.