

1 LOCATION OF WATER WELL: Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4		16		T 26 S 2	
Distance and direction from nearest town or city street address of well if located within city?							
230 E. Chicago, Colwich							
2 WATER WELL OWNER: Ewertz Oil							
RR#, St. Address, Box # : 230 E. Chicago				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Colwich, KS 67030				Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 30.5 ft. ELEVATION: 1384.13 TOC					
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.					
		WELL'S STATIC WATER LEVEL 25.38 ft. below land surface measured on mo/day/yr 1-27-03					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 8.5 in. to 30.5 ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
7 Fiberglass Threaded Flush							
Blank casing diameter 4 in. to 15.5 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface Flush in., weight 2 lbs./ft. Wall thickness or gauge No. Sch 40							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)							
12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 30.5 ft. From ft. to ft.							
From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 13.5 ft. to 30.5 ft. From ft. to ft.							
From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete							
Grout Intervals From 0 ft. to 0.5 ft. From 0.5 ft. to 13.5 ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/ Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? How many feet?							
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 1 Asphalt							
1 19 Clay, dark brown, slightly sandy							
19 30.5 Sand, med. to coarse grained							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 1-22-03 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 2-14-03							
under the business name of Geotechnical Services, Inc. by (signature)							
INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							