


Muzaa

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Fraction: <u>NW 1/4 NW 810</u> Section Number: <u>1</u> Township Number: <u>26</u> Range Number: <u>2</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>135th W. & 1st N. 1/2 NE 1/8 E</u>	
2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code <u>Chase Transportation</u> <u>1750 N. MacArthur Suite 120</u> <u>Irving, TX 75063</u>	
Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	
4 DEPTH OF COMPLETED WELL: <u>25</u> ft. ELEVATION: Depth(s) Groundwater Encountered: <u>91</u> ft. 2 <u>7-17-04</u> ft. 3 <u>7-17-04</u> ft. WELL'S STATIC WATER LEVEL: <u>91</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>91</u> ft. after <u>7-17-04</u> hours pumping <u>91</u> gpm Est. Yield <u>91</u> gpm: Well water was <u>91</u> ft. after <u>7-17-04</u> hours pumping <u>91</u> gpm WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>	
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) Blank casing diameter <u>2</u> in. to <u>15</u> ft., Dia <u>15</u> in. to <u>40</u> ft., Dia <u>40</u> in. to <u>40</u> ft., Dia Casing height above land surface <u>40</u> in., weight <u>40</u> lbs./ft. Wall thickness or gauge No. <u>40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>5</u> ft., From <u>5</u> ft. to <u>5</u> ft., From <u>5</u> ft. to <u>5</u> ft., From <u>5</u> ft. to <u>5</u> ft. GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>3</u> ft., From <u>3</u> ft. to <u>3</u> ft., From <u>3</u> ft. to <u>3</u> ft., From <u>3</u> ft. to <u>3</u> ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>2</u> ft. to <u>0</u> ft., From <u>3</u> ft. to <u>2</u> ft., From <u>2</u> ft. to <u>2</u> ft., From <u>2</u> ft. to <u>2</u> ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? How many feet? <u>Open field</u>	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS <u>0 8 Brown sandy clay</u> <u>8 25 Brown wet medium to coarse sand w/some gravel</u>	
RECEIVED OCT 04 2004 BUREAU OF WATER	