

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u> Section: <u>SW 1/4 NW 1/4 NW 1/4</u> Township Number: <u>2</u> Range Number: <u>2</u> E/W: <u>W</u>
--

Distance and direction from nearest town or city street address of well if located within city?

2210 N. 142nd W. Cornich, KS2 WATER WELL OWNER: John JoinerRR#, St. Address, Box # : Imbler Estates, Cornich, KS 67030
City, State, ZIP CodeBoard of Agriculture, Division of Water Resources
Application Number:3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 35 ft. ELEVATION:Depth(s) Groundwater Encountered: 10 ft. 2 ft. 3 ft.WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 25 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 9 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes 0 No5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 25 ft. Dia 12 in. to ft. Dia 160 P.S.F.Casing height above land surface 12 in., weight 2.4 lbs./ft. Wall thickness or gauge No. 160 P.S.F.

TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-Cement

1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) PVC

2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From ft. to 35 ft. From ft. to ft.GRAVEL PACK INTERVALS: From 10 ft. to 35 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Heat cement 10 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? South How many feet? 100

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	1	top soil
1	2	clay
2	10	fine sand
10	35	gravel/sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/30/05 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No. #740 This Water Well Record was completed on (mo/day/yr) 1-1-05under the business name of Wenger Drilling Inc by (signature) Michael Wenger