Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SWSW 2 1/4 26 1/4 Т 2WS E/W Distance and direction from nearest town or city street address of well if located within city? 15121 W. 70th Ct. No. Colwich, Kansas HARSHBERGER, Jason WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 15121 W. 70th Ct. No. Colwich, Kansas CITY, STATE: ZIP CODE Application Number: 85 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. **ELEVATION** Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 27 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 8/13/15 Pump test data: Well water was NW NE ft. after hours of pumping @ apm Est. Yield: gpm Well water was ft. after hours of pumping @ apm Ξ Bore Hole Diameter 12 to 85 in. and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below) 2. Irrigation 4 Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well disposal ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) submitted Was Water Well Disinfected? (YES) NO TYPE OF CASING USED: 5 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter to 65 ft., Dia. Dia in. ft. to Casing height above land surface: 12 in . Weight: 2.35 lbs. / ft. Wall thickness or gauge No .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9. ABS 11. Other (specify) 5. Fiberglass 1 Steel 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 8. Saw cut 4. Key punched 6. Wire wrapped 10. Other (specify) SCREEN - PERFORATION INTERVAL 65 85 ft From to ft., From ft. ft to ft. From to ft., From ft ft. to 24 **GRAVEL PACK INTERVALS:** ft. to 85 From ft., From to ft. From ft. to ft., From ft to ft. GROUT MATERIALS 6 Other 1. Neat cement 2. Cement Grout bentonite hole plug 3. Bentonite Grout Intervals: ft. 24 From ft.. ft. to ft., From to ft What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 6. Seepage pit 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line South Direction from well? How many feet? 75 ft plus From LITHOLOGIC LOG Τо From To LITHOLOGIC LOG 0 topsoil clay 18 40 fine sand 40 50 clav 50 60 fine sand 60 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 8-13-15 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief

Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8-17-2015 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb