

1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 SE 1/4 Section Number 2 Township Number 26 Range Number 20
County Sedgwick
Distance and direction from nearest town or city street address of well if located within city?
See Below
2 WATER WELL OWNER: STEVE CAMFIELD
RR#, St. Address, Box # : 7231 No 135th West
City, State, ZIP Code : MAIZE KS 67101
Board of Agriculture, Division of Water Resources
Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 12 ft. 2. 12 ft. 3. 12 ft.
WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 9-17-90
Pump test data: Well water was 12 ft. after 16 hours pumping 20 gpm
Est. Yield 50 gpm: Well water was 12 ft. after 16 hours pumping 20 gpm
Bore Hole Diameter 11 in. to 43 ft. and 43 in. to 43 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
2 PVC 4 ABS 7 Fiberglass Threaded X
Blank casing diameter 5 in. to 33 ft. Dia 33 in. to 33 ft. Dia 33 in. to 33 ft. Dia 33 in. to 33 ft. Dia
Casing height above land surface 12 in. weight 259 lbs./ft. Wall thickness or gauge No Sch 40 160AS
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 33 ft. to 43 ft. From 33 ft. to 43 ft. From 33 ft. to 43 ft. From 33 ft. to 43 ft.
GRAVEL PACK INTERVALS: From 15 ft. to 43 ft. From 15 ft. to 43 ft. From 15 ft. to 43 ft. From 15 ft. to 43 ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout intervals: From 3 ft. to 15 ft. From 3 ft. to 15 ft. From 3 ft. to 15 ft. From 3 ft. to 15 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? West How many feet? 120
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 Top soi.
2 8 clay
8 24 fine sand.
24 25 clay
25 43 gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-17-90 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 1318 This Water Well Record was completed on (mo/day/yr) 10-2-90
under the business name of Wenger & Bully by (signature) [Signature]
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-8545. Send one to WATER WELL OWNER and retain one for your records.