

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County <u>SEDGWICK</u> Fraction <u>SE 1/4 NE 1/4 SE 1/4</u> Section number <u>13</u> Township number <u>26</u> Range number <u>9</u> N E/W	
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>5551 W. 119TH W. MAIZE KANS</u>	
3. Owner of well: <u>BERT + WETRA SALES INC.</u> R.R. or street: <u>5551 N 119TH WEST</u> City, state, zip code: <u>MAIZE KANS 67101</u>	
4. Locate with "X" in section below: Sketch map: <u>DRILLED 9" HOLE TO 13' THEN 6" HOLE TO 18' - INSTALLED CASING + COMPLETED WITH SAND BUCKET</u>	
6. Bore hole dia. <u>9</u> in. Completion date <u>3-2-79</u> Well depth <u>41</u> ft. <u>GRADE</u>	
7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary	
8. Use: ☒ Domestic ☐ Public supply ☒ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
9. Casing: Material <u>RMP</u> Height: Above or below <u>16</u> in. Threading: <u>Welded</u> Surface <u>16</u> in. RMP <u>1</u> PVC <u>1.55</u> lbs./ft. Dia. <u>5</u> in. to <u>41</u> ft. depth Wall Thickness: inches or <u>200</u> Dia. <u>5</u> in. to <u>41</u> ft. depth gage No. <u>200</u>	
10. Screens: Manufacturer's name <u>SUNFLOWER</u> Type <u>RMP</u> Dia. <u>5 INCH</u> Slot/gauze <u>3/8</u> Length <u>7 FT</u> Set between <u>34</u> ft. and <u>41</u> ft. Gravel pack? <u>NO</u> Size range of material <u>20/30</u>	
11. Static water level: <u>19</u> ft. below land surface Date <u>3-7-79</u> mo./day/yr.	
12. Pumping level below land surfaces: <u>NA</u> ft. after <u>NA</u> hrs. pumping g.p.m. Estimated maximum yield <u>70</u> g.p.m.	
13. Water sample submitted: <u>NO</u> Yes ☒ No ☐ Date <u>3-7-79</u> mo./day/yr.	
14. Well head completion: <u>WELL HEAD</u> Pitless adapter <u>16</u> inches above grade	
15. Well grouted? <u>YES</u> With: <u>Neat cement</u> Bentonite ☒ Concrete ☐ Depth: From <u>-3</u> ft. to <u>-13</u> ft.	
16. Nearest source of possible contamination: <u>AT LEAST 100</u> ft. Direction <u>EAST</u> Type <u>SEWER</u> Well disinfected upon completion? ☒ Yes ☐ No	
17. Pump: ☒ Not installed Manufacturer's name <u>BEARDEN PUMP & WELL</u> Model number <u>312</u> HP <u>MENTOR</u> Volts <u>WICHITA</u> Length of drop pipe <u>312</u> ft. capacity <u>312</u> g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
18. Elevation: <u>1300 FT</u> Topography: ☒ Hill ☐ Slope ☐ Upland ☒ Valley	
19. Remarks: <u>CUSTOMER WILL BUILD 4" X 4" X 4" SLAB AROUND WELL WELL WILL BE USED IN PLANT AND FOR TOILET USE + FOR HUMAN CONSUMPTION - AS STAND BY WELL W.B.</u>	
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>BEARDEN PUMP & WELL</u> Business name <u>312 MENTOR</u> License No. <u>WICHITA</u> Address <u>312 MENTOR</u> Signed <u>Ob W Beard</u> Date <u>3/10/79</u> Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5