

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>N 1/4 NE 1/4 SE 1/4</u>	Section Number <u>13</u>	Township Number T <u>26</u> S	Range Number R <u>2</u> E
Distance and direction from nearest town or city street address of well if located within city? <u>Coleman Plant Maize KS GW10</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : <u>P.O. Box 1762 Wichita KS</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL <u>14</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was .ft. after . hours pumping gpm			
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to <u>19</u> ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No			
1 Steel <u>2 PVC</u> Blank casing diameter .in. to .ft. Casing height above land surface .in., weight lbs./ft. Wall thickness or gauge No.		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 4 ABS 7 Fiberglass Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot <u>3 Mill slot</u> 2 Louvered shutter 4 Key punched		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:					
From .ft. to .ft.		From .ft. to .ft.			
GRAVEL PACK INTERVALS:					
From .ft. to .ft.		From .ft. to .ft.			
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other					
Grout Intervals: From .ft. to .ft.		From .ft. to .ft.			
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit. 9 Feedyard		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 17 Other (specify below)			
Direction from well? <u>Within</u>		How many feet? <u>within</u>			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 8 clay					
8 TD sand, gravel					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/21/92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>102</u> This Water Well Record was completed on (mo/day/yr) <u>12/17/92</u> under the business name of <u>Rayne</u> by (signature) <u>[Signature]</u>					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.