

1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 16 Township Number T 26 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
316 No Colorado Colwich KS

2 WATER WELL OWNER: Holt Const.
 RR#, St. Address, Box #: 2801 W. Central
 City, State, ZIP Code: Wichita, KS 67203
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
---	NW	---	NE

---	SW	---	SE

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 27 ft.
 Depth(s) Groundwater Encountered 1. 27 ft. 2. 28 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 7/28/81
 Pump test data: Well water was 28 ft. after 12 hours pumping 20 gpm
 Est. Yield 30 gpm: Well water was 28 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 60 ft. and 60 in. to 60 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel ☐ 3 RMP (SR) ☒ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued X Clamped X
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded
 7 Fiberglass ☐ Threaded Threaded
 Blank casing diameter 5 in. to 52 ft. Dia. 52 in. to 60 ft. Dia. 60 in. to 60 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SAR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 7 PVC ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☒ 11 Other (specify) None
 9 ABS ☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) None
 SCREEN-PERFORATED INTERVALS: From 52 ft. to 60 ft. From 60 ft. to 60 ft.
 From 60 ft. to 60 ft. From 60 ft. to 60 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 60 ft. From 60 ft. to 60 ft.
 From 60 ft. to 60 ft. From 60 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☒ 3 Bentonite ☐ 4 Other ☐
 Grout Intervals: From 3 ft. to 13 ft. From 13 ft. to 60 ft. From 60 ft. to 60 ft. From 60 ft. to 60 ft.
 What is the nearest source of possible contamination:
 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☐
 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐
 3 Watertight sewer lines ☒ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) None
 13 Insecticide storage ☐
 Direction from well? No How many feet? 20

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top 50.			
2	24	Red clay			
24	35	med sand			
35	36	Red clay			
36	45	med sand			
45	46	Red clay			
46	60	coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-28-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-31-81 under the business name of Wenger Pilling by (signature) Wenger Pilling

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.