


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 16 Township Number T 26 S Range Number R 2 EW
 County: Logansport
 Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: al mayeske
 RR#, St. Address, Box #: 320 No Colorado
 City, State, ZIP Code: Colwich KS 67030
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 7-28-81
 Pump test data: Well water was 27 ft. after 12 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 11 in. to 60 ft., and in. to ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR)
 2 PVC ☐ 4 ABS
 5 Wrought iron ☐ 6 Asbestos-Cement ☐ 7 Fiberglass
 8 Concrete tile ☐ 9 Other (specify below)
 CASING JOINTS: Glued X Clamped
 Welded
 Threaded.
 Blank casing diameter 5 in. to 52 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☒ 8 RMP (SR)
 9 ABS ☐ 10 Asbestos-cement
 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☒ 3 Mill slot
 2 Louvered shutter ☐ 4 Key punched
 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
 6 Wire wrapped ☐ 9 Drilled holes
 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 52 ft. to 60 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 60 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 13 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SE How many feet? 20

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
3	23	Red clay			
23	35	med sand			
35	36	Red clay			
36	45	med sand			
45	46	Red clay			
46	60	coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-28-81 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 7318 This Water Well Record was completed on (mo/day/yr) 7-31-81
 under the business name of Weninger Duller by (signature) [Signature]
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

16

NW 1/4

NE 1/4

SE 1/4