


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NE 1/4 Section Number 16 Township Number T 26 S Range Number R 20 EW
 County: Edgewood Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: DALE SIMON
 RR#, St. Address, Box #: 610 WHEATLAND Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: COI WICH KS 67030 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 
 4 DEPTH OF COMPLETED WELL: 57 ft. ELEVATION: 28 ft. below land surface measured on 7-16-90
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 20 ft.
 WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on 7-16-90
 Pump test data: Well water was 28 ft. after 12 hours pumping 20 gpm
 Est. Yield 70 gpm: Well water was 28 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 57 ft. and 57 in. to 57 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
☒ 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
☒ 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
 2 PVC 4 ABS 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 47 ft. Dia 1.59 in. to 57 ft. Dia 50R-26
 Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No 50R-26
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 6 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 47 ft. to 57 ft. From 47 ft. to 57 ft.
 From 23 ft. to 57 ft. From 23 ft. to 57 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 57 ft. From 23 ft. to 57 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 57 ft. From 57 ft. to 57 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? EAST How many feet? 20

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soil			
2	19	Clay			
19	34	fine sand			
34	36	clay			
36	57	med gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-16-90 and this record is true to the best of my knowledge and belief, Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 7-16-90
 under the business name of Wenger Dully by (signature) [Signature]