


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 SE 1/4 Section Number 16 Township Number T 26 S Range Number R 2 E
 County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? SE Bulow

2 WATER WELL OWNER: Cy Stigman
 RR#, St. Address, Box #: 412 Central
 City, State, ZIP Code: Colwich KS 67030 Board of Agriculture, Division of Water Resources
 Application Number: 58

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 58 ft. ELEVATION: 55.93 ft.
 Depth(s) Groundwater Encountered 1. 17 ft. 2. 55.93 ft. 3. 55.93 ft.
 WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 58 ft. after 55.93 hours pumping 55.93 gpm
 Est. Yield 58 gpm: Well water was 58 ft. after 55.93 hours pumping 55.93 gpm
 Bore Hole Diameter 58 in. to 58 ft., and 58 in. to 58 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 5 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 58 in. to 58 ft., Dia. 58 in. to 58 ft., Dia. 58 in. to 58 ft.
 Casing height above land surface 58 in., weight 58 lbs./ft. Wall thickness or gauge No. 160 PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 58 ft. to 58 ft., From 58 ft. to 58 ft.
 GRAVEL PACK INTERVALS: From 17 ft. to 58 ft., From 58 ft. to 58 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 17 ft., From 17 ft. to 58 ft., From 58 ft. to 58 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Septage pit 9 Feedyard 13 Insecticide storage
 Direction from well? South How many feet? 15'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	16	clay			
16	32	sand			
32	34	clay			
34	55	med sand			
55	56	clay			
56	58	fine sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-5-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-6-93 under the business name of Weninger Drilling Inc by (signature) Stan R. Weninger

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4