

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	16	T 26 S	R 02 (W)
Distance and direction from nearest town or city street address of well if located within city? Ewertz Oil Co. 230 E. Chicago, Colwich, Ks. 67030					

2 WATER WELL OWNER: George Ewertz		Board of Agriculture, Division of Water Resources Application Number:
RR#, St. Address, Box #: 230 E. Chicago		
City, State, ZIP Code: Colwich, KS. 67030		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 33'6" ft. ELEVATION:	
		Depth(s) Groundwater Encountered: 24'6" ft. 2. ft. 3. ft.	
		WELL'S STATIC WATER LEVEL: 24.84 ft. below land surface measured on mo/day/yr 4-18-94	
		Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm	
		Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm	
Bore Hole Diameter: 8 1/2" in. to 33'6" ft., and _____ in. to _____ ft.		WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes _____ No X If yes, mo/day/yr sample was submitted _____			
Water Well Disinfected? Yes _____ No (X)			

5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued _____ Clamped _____	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded _____		Threaded X	
2 PVC 4 ABS 7 Fiberglass			
Blank casing diameter 2.375 in. to 18' ft. Dia _____ in. to _____ ft. Dia _____ in. to _____ ft.			
Casing height above land surface Flush Mount in., weight _____ lbs./ft. Wall thickness or gauge No. SDR-13			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement Sch 40		11 Other (specify) _____	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify) _____	
2 Louvered shutter 4 Key punched 7 Torch cut			
SCREEN-PERFORATED INTERVALS: From 33' ft. to 18' ft. From _____ ft. to _____ ft.			
GRAVEL PACK INTERVALS: From 33'6" ft. to 16' ft. From _____ ft. to _____ ft.			

6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 16' ft. to 4' ft. From 4' ft. to 0' ft. From _____ ft. to _____ ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard			
Direction from well? South		How many feet? 15'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
.0	4.75	Dk brn-med brn tight dry clay, earthy odor, roots, root casts, earthy worm burrows, iron oxides.			
4.75	10	Med rust stained brn clay, stiff, tight, earthy odor, iron oxides.			
10	18.50	Orange brn sandy silty clay, dry, tight, hard, earthy odor, iron oxides.			
18.50	33'6"	Red brn sand, fine-med. grained, dry, no odor. Wet at 24 1/2'.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/18/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 4-28-94 under the business name of JB Environmental Drilling by (signature) James Bieber	
---	--