

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 16	Township Number T 26 S	Range Number R 2 EW
Distance and direction from nearest town or city street address of well if located within city? Ewertz Oil Co. 230 E. Chicago, Colwich, KS. 67030					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		George Ewertz 230 E. Chicago Colwich, KS. 67030 Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 33A ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 24' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 23.18 ft. below land surface measured on mo/day/yr 4-19-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 33" ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes (N)			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 2.375 in. to 17'6" ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SDE-13 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement Sch 40 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 33' ft. to 18' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 33' ft. to 15' ft., From ft. to ft. From ft. to ft., From ft. to ft.			
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 15' to 4' ft., From 4' to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 3 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? West How many feet? 150'					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	.50	Asphalt			
.50	5.50	Dk brn silty clay, moist, earthy odor, friable.			
5.50	12.50	Red brn silty clay, moist, no odor, increasing fine grained sand content w/ depth, no odor.			
12.50	18	Reddish brn sandy clay to clayey sand, moist, no odor, fine grained sand.			
18	33	Fine-med tan sand, dry, no odor Wet at 24', slight to mod odor. slight discolored sands			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/19/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 4-28-94 under the business name of JB Environmental Drilling by (signature) James Baker					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4