

1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 SE 1/4 Section Number 16 Township Number 26 S Range Number 2 EW

Distance and direction from nearest town or city street address of well if located within city?

133 W. Colwich Colwich KS.

2 WATER WELL OWNER:

RR#, St. Address, Box #


City, State, ZIP Code

BILL SADOWSKIE
4449 GUNNISON
WICHITA KS 67220

Board of Agriculture, Division of Water Resources

Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 27 ft. 2. 27 ft. 3. 27 ft.

WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 5/11/91

Pump test data: Well water was 27 ft. after 1/2 hours pumping 620 gpm

Est. Yield 70 gpm: Well water was 27 ft. after 1/2 hours pumping 620 gpm

Bore Hole Diameter: 11 in. to 65 ft. and 65 in. to 65 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
<u>1 Domestic</u>	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:

- 1 Steel
2 PVC
3 RMP (SR)
4 ABS

- 5 Wrought iron
6 Asbestos-Cement
7 Fiberglass
8 Concrete tile
9 Other (specify below)

- CASING JOINTS: Glued X Clamped
Welded
Threaded

Blank casing diameter 5 in. to 58 ft. Dia 58 in. to 65 ft. Dia 65 in. to 65 ft. Dia

Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160 MC

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel
2 Brass
3 Stainless steel
4 Galvanized steel

- 5 Fiberglass
6 Concrete tile
7 PVC
8 RMP (SR)
9 ABS

- 10 Asbestos-cement
11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot
2 Louvered shutter
3 Mill slot
4 Key punched

- 5 Gauzed wrapped
6 Wire wrapped
7 Torch cut

- 8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 58 ft. to 65 ft. From 65 ft. to 65 ft. From 65 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 23 ft. to 65 ft. From 65 ft. to 65 ft. From 65 ft. to 65 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout intervals: From 3 ft. to 23 ft. From 23 ft. to 65 ft. From 65 ft. to 65 ft. From 65 ft. to 65 ft.

What is the nearest source of possible contamination:

- 1 Septic tank
2 Sewer lines
3 Watertight sewer lines
4 Lateral lines
5 Cess pool
6 Seepage pit

- 7 Pit privy
8 Sewage lagoon
9 Feedyard

- 10 Livestock pens
11 Fuel storage
12 Fertilizer storage
13 Insecticide storage
14 Abandoned water well
15 Oil well/Gas well
16 Other (specify below)

Direction from well?

South

How many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top So.			
2	20	CLAY			
20	34	fine SAND.			
34	35	CLAY			
35	65	fine to med SAND.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-11-91 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 1318

This Water Well Record was completed on (mo/day/yr) 5-22-91

under the business name of Weninger Pully

by (signature) [Signature]