

NE SW NW SE

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>	<u>N 1/4 S 1/4 E 1/4</u>	<u>16</u>	<u>T 26 S</u>	<u>R 2 E</u>

Distance and direction from nearest town or city street address of well if located within city?

615 Brookside Colwich KS.

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Application Number:
City, State, ZIP Code :	

MARCO INC.3215 W. CentralWichita KS 67203.

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
--	---------------------------	------------

N	1	2	3	4
5	6	7	8	9
10	11	12	13	14
15	16	17	18	19
20	21	22	23	24

Depth(s) Groundwater Encountered	1	2	3	4
WELL'S STATIC WATER LEVEL	23	ft. below land surface measured on	11-12-80	
Pump test data: Well water was	25	ft. after	12	hours pumping
Est. Yield	50	gpm: Well water was		ft. after
Bore Hole Diameter	11	in. to	58	ft. and
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well	
	1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering
	2 Irrigation	4 Industrial	7 Lawn and garden only	10 Observation well
Was a chemical/bacteriological sample submitted to Department?	Yes	No	X	
Water Well Disinfected?	Yes	X	No	

5 TYPE OF BLANK CASING USED:	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	X	Clamped
1 Steel	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded		
2 PVC	7 Fiberglass			Threaded		
Blank casing diameter	5	in. to	48	ft. Dia		
Casing height above land surface	12	in., weight	1.59	lbs./ft. Wall thickness or gauge No.	SPR-26	

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)

SCREEN-PERFORATED INTERVALS:	From	48	ft. to	58	ft. From		ft. to		ft.
GRAVEL PACK INTERVALS:	From	15	ft. to	58	ft. From		ft. to		ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other					
Grout Intervals:	From	5	ft. to	15	ft. From		ft. to		ft.

What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?	West	How many feet?	35	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	top soil			
2	21	red clay			
21	33	fine sand			
33	35	red clay			
35	58	med. gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)	11-12-80	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No.	318	This Water Well Record was completed on (mo/day/yr)
under the business name of	Alminger, Phillip	by (signature)
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.		