


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 21 Township Number T 26 S Range Number R 2 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 1/2 mile South 1/2 West Colwich Ks.

2 WATER WELL OWNER: Dave Hemman
 RR#, St. Address, Box #: R#1
 City, State, ZIP Code: Colwich Ks. 67030
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 ft. 28 ft. 3. ft. ft.
 WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 5-12-88
 Pump test data: Well water was 28 ft. after 2 hours pumping 20 gpm
 Est. Yield 70 gpm: Well water was 28 ft. after 2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 60 ft., and 60 in. to 60 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☐ 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X
☐ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X
☐ 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 50 ft. Dia. 50 in. to 50 ft. Dia. 50 in. to 50 ft.
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 8 RMP (SR) ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 7 Torch cut ☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From 50 ft. to 60 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 60 ft., From 23 ft. to 60 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout intervals: From 3 ft. to 23 ft., From 23 ft. to 60 ft., From 60 ft. to 60 ft.
 What is the nearest source of possible contamination:
☒ 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? EAST
 How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	24	clay			
24	32	fine sand			
32	33	clay			
33	60	fine to med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-12-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-29-88
 under the business name of Weninger Drilling by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4