


1 LOCATION OF WATER WELL: Fraction NE 1/4 SW 1/4 NE 1/4 Section Number 21 Township Number T 26 S Range Number R 2 E
 County: Sedgwick

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Rick Easter
 RR#, St. Address, Box #: 618 Cardinal Ln.
 City, State, ZIP Code: Colwich, KS. 67030
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 36-82 ft.

Depth(s) Groundwater Encountered 1. 28 ft. 2. 30 ft. 3. 30 ft.

WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 3-6-82

Pump test data: Well water was 30 ft. after 12 hours pumping 20 gpm

Est. Yield 30-40 gpm: Well water was 30 ft. after 12 hours pumping 20 gpm

Bore Hole Diameter: 11 in. to 80 ft. and 20 in. to 80 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SB) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped X Welded X Threaded X

Blank casing diameter 5 in. to 70 ft. Dia 12 in. to 159 lbs./ft. Wall thickness or gauge No. SDR-26

Casing height above land surface 12 in., weight 159 lbs./ft.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SB) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. From 70 ft. to 80 ft. From 70 ft. to 80 ft.

GRAVEL PACK INTERVALS: From 16 ft. to 80 ft. From 16 ft. to 80 ft. From 16 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 6 ft. to 16 ft. From 16 ft. to 80 ft. From 16 ft. to 80 ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer line 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? East How many feet? 30

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 2 Top Soil

2 31 Red Clay

31 38 Fine Sand

38 43 Red Clay

43 62 Fine Sand

62 63 Red Clay

63 80 Med. GRAVEL

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-6-82 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 3182 This Water Well Record was completed on (mo/day/yr) 3-30-82

under the business name of Weninger DRILLING by (signature) Weninger

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

26

R

1

END

SEC.

21

NE 1/4

SW 1/4

NE 1/4