


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 22 Township Number T 26 S Range Number R 2 W
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city? 1 E 1 So. Colwich Ks.

2 WATER WELL OWNER: Edwin Freund.
RR#, St. Address, Box #: R# Colwich, Ks 67030
City, State, ZIP Code: Colwich, Ks 67030
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 64 ft. ELEVATION: 28 ft. below land surface measured on mo/day/yr 1-22-90
Depth(s) Groundwater Encountered 1. 27 ft. 2. 28 ft. 3. 20 ft.
WELL'S STATIC WATER LEVEL: 28 ft. below land surface measured on mo/day/yr 1-22-90
Pump test data: Well water was 28 ft. after 12 hours pumping 20 gpm
Est. Yield 60 gpm: Well water was 28 ft. after 12 hours pumping 20 gpm
Bore Hole Diameter: 11 in. to 64 ft., and 64 in. to 64 ft.
WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 11 Injection well
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued Clamped
2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded
Blank casing diameter 5 in. to 51 ft., Dia. 51 in. to 51 ft., Dia. 51 in. to 51 ft., Dia. 51 in. to 51 ft.
Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 5 DR 26
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 6 RMP (SR) ☐ 7 PVC ☐ 10 Asbestos-cement
2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot ☐ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐ 10 Other (specify) 12 None used (open hole)
SCREEN-PERFORATED INTERVALS: From 51 ft. to 64 ft., From 51 ft. to 64 ft., From 51 ft. to 64 ft., From 51 ft. to 64 ft.
GRAVEL PACK INTERVALS: From 23 ft. to 64 ft., From 23 ft. to 64 ft., From 23 ft. to 64 ft., From 23 ft. to 64 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other 90
Grout Intervals: From 3 ft. to 23 ft., From 23 ft. to 64 ft., From 23 ft. to 64 ft., From 23 ft. to 64 ft.
What is the nearest source of possible contamination:
1 Septic tank ☒ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
Direction from well? North
How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top So.			
2	20	clay			
20	26	fine SAND			
26	30	clay			
30	41	fine SAND			
41	43	clay			
43	64	fine to coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-22-90 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 1318 This Water Well Record was completed on (mo/day/yr) 1-22-90
under the business name of Weninger Drilling by (signature) Weninger