


1 LOCATION OF WATER WELL: Sedgwick		FRACTION SW 1/4 NE 1/4 NE 1/4		Section Number 23		Township Number T 26 S		Range Number R 2W E/W			
Distance and direction from nearest town or city street address of well if located within city? 1.8 mile East of and .2 South of Colwich, Kansas Colwich, Kansas											
2 WATER WELL OWNER: NC + HYBRIDS		RR#, ST. ADDRESS, BOX #: 207 E. Wichita, Box 428				Board of Agriculture, Division of Water Resource					
CITY, STATE, ZIP CODE: Colwich, Kansas		67030		Application Number: 2954							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 4-16-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 1,500 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 80 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded Blank casing Diameter 16 in. to 40 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 19.750 lbs. / ft. Wall thickness or gauge No. .616 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 40 ft. to 80 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 80 ft., From ft. to ft. from ft. to ft., From ft. to ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0	2			topsoil							
2	8			brown clay							
8	11			fine, silty sand							
11	20			fine to medium sand							
20	35			fine to medium and some coarse sand							
35	45			medium sand							
45	65			medium to coarse sand and fine gravel							
65	80			medium to coarse sand and medium gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/16/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/30/94 Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>											