

1 LOCATION OF WATER WELL: Fraction SE SW NE Section Number 36 Township Number T 26 S Range Number R 2 E/W
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: Steve Hill
 RR#, St. Address, Box # 313 N. 124th W.
 City, State, ZIP Code Wichita, KS 67223
 Board of Agriculture, Division of Water Resources
 Application Number: 66

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
 4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 28 ft. below land surface measured on mo/day/yr
 Depth(s) Groundwater Encountered 1. 28 ft. 2. 28 ft. 3. 2-28-95 ft.
 WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 11 ft. after 112 hours pumping 2-28-95 gpm
 Est. Yield 30 gpm Well water was 66 ft. after 112 hours pumping 2-28-95 gpm
 Bore Hole Diameter 11 in. to 66 ft. and 66 in. to 66 ft.
 WELL WATER TO BE USED AS:
 1 Domestic X 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
 Blank casing diameter 5 in. to 22 ft. Dia 2.60 in. to 2.60 ft. Dia 160 PSI lbs./ft. Wall thickness or gauge No.
 Casing height above land surface 12 in. weight 2.60 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 22 ft. to 66 ft. From 66 ft. to 66 ft. From 66 ft. to 66 ft.
 GRAVEL PACK INTERVALS: From 3 ft. to 66 ft. From 66 ft. to 66 ft. From 66 ft. to 66 ft.

6 GROUT MATERIAL: 0 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 3 ft. From 3 ft. to 3 ft. From 3 ft. to 3 ft. From 3 ft. to 3 ft.
 What is the nearest source of possible contamination:
Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Southwest How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	clay			
22	33	fine sand			
33	34	clay			
34	66	fine to medium Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-28-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 3-6-95 under the business name of Weninger Drilling, Inc. by (signature) Karrina Morrison