## WATER WELL RECORD Form WWC-5 KSA 82a-1212

10 S. 3 W. OF KINSLEY, KS 2 WATER WELL DWNER: GLENN HE					
RR#, St. Address, Box # :		Board of	Agriculture, D	)ivision of ₩	later Resources
City, State, ZIP code : OFFERLE,		Applicati	ion Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	! 4 DEPTH OF COMPLETED WELL	ELEVAT	TION:		
1   NW NE	: Pumo testdata: I	<b>41</b> ft. below l Well water was	land surface me ft. after	easured on mo hours	o/day/yr s pumping g
1 1 1 1	Estimated Yield opm:	Well water was	ft. after	hours	onwbing a
M ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	;   Bore Hole Diameter	8.75 in. to 8	30 ft., and	in. to	ft.
	: ; Well water to be used as: (	01 DOMESTIC			
SW  SE  	Was a chemical/bacteriolog	ical sample submi as submitted	itted to depart		l disinfected? Y
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs.	GLUED to ft D	Dia in. t	o ft.	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS:	CASING JOINTS: 0 to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft., D  /ft. Wall thickn  . From ft From ft.	Dia in.t ness or gauge N to ft. to ft.	o ft. Io. <b>26</b>	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:	CASING JOINTS: 0 to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft., D  /ft. Wall thickn  . From ft. , From ft. , From ft.	Dia in. t ness or gauge N to ft. to ft. to ft.	o ft. Io. <b>26</b>	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possil	CASING JOINTS: 0 to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft., D  /ft. Wall thickn  . From ft From ft From ft From ft.	Dia in. t ness or gauge N to ft. to ft. to ft. to ft.	ft.	
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  GRAVEL PACK INTERVALS: GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possil Direction from well? ALL	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft D  /ft. Wall thickn  . From ft From ft From ft From ft From ft From ft.	Dia in. to ess or gauge Notes of the est of	ft.	w many feet?
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possil Direction from well? ALL  FROM : TO :  3 : SILT & SAND 3 : 12 : TAN CLAY	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft., D  /ft. Wall thickn  . From ft From ft From ft From ft.	Dia in. t ness or gauge N to ft. to ft. to ft. to ft.	ft.	w many feet?
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possil Direction from well? ALL  FROM : TO : : : : : : : : : : : : : : : : :	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft D  /ft. Wall thickn  . From ft From ft From ft From ft From ft From ft.	Dia in. to ess or gauge Notes of the est of	ft.	w many feet?
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possib Direction from well? ALL  FROM	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft D  /ft. Wall thickn  . From ft From ft From ft From ft From ft From ft.	Dia in. to ess or gauge Notes of the est of	ft.	w many feet?
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possil Direction from well? ALL  FROM : TO :	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft D  /ft. Wall thickn  . From ft From ft From ft From ft From ft From ft.	Dia in. to ess or gauge Notes of the est of	ft.	w many feet?
TYPE OF BLANK CASING USED: 02 PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER: SCREEN OR PERFORATION OPENINGS ARE:  SCREEN PERFORATED INTERVALS:  GRAVEL PACK INTERVALS:  GROUT MATERIAL 03 BENTONITE Grout Intervals: From ft. to What is the nearest source of possib Direction from well? ALL  FROM	CASING JOINTS: ( to 70 ft., Dia in. 12 in., weight lbs. AL: 07 PVC	GLUED  to ft D  /ft. Wall thickn  . From ft From ft From ft From ft From ft From ft.	Dia in. to ess or gauge Notes of the est of	ft.	w many feet?