LOCATION OF WATER WELL: Frac COUNTY: EDWARDS HE	tion 1/4 ME 1/4 ME	1/4 ¦ 19	ection Number	† Township † T 26	Number S	Range Kumber R 20 W
Distance and direction from nearest 7 1/2 NILES SOUTH OF OFFERLE	town or city street	address of we	ell if locate	d within city?		
WATER WELL OWNER: WETZEL, RR#, St. Address, Box #: RR 1, BO			Board of	Agriculture, D	ivision of Wa	ater Resources
City, State, ZIP code : OFFERLE,	KS 67563-		Applicat:	ion Number:		1
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	Depth(s) Groun	dwater Encount	ered 1	. 0 ft.	2. 0 ft.	3. 0 f
\	WELL'S STATIC WA	TER LEVEL 1 estdata: Well	8 ft. below : water was	land surface mea O ft. after	asured on n o/ O hours	day/yr 08/02/03/ pumping 0 g
	! Estimated Yield	0 apm: Wel	l water was	0 ft. after	A hours	numping () gr
W	1			40 ft., and	in. to	0 ft.
SW SE	WELL WATER TO BE	USED AS: LAWN	& GARDEN			!
/	Was a chemical/b If yes, mo/day/y	acteriological r sample was s	sample submitubmitted	itted to departu	ment? Wo ; Water well	disinfected? Y
Blank casing diameter 5 in Casing height above land surface	. to 35 ft., Dia 12 in., weight	in. to	0 ft., I	Dia in. to ness or gauge No	0 ft. 0. 26	
Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER. SCREEN OR PERFORATION OPENINGS ARE:	. to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft.	to 0 ft.	0 ft. 0. 26	
TYPE OF BLANK CASING USED: PVC Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS:	. to 35 ft., Dia 12 in., weight IAL: PVC	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr	Oft., I Wall thicks on Oft. on Oft. on Oft.	to 0 ft. to 0 ft. to 0 ft.	0 ft. 0. 26	
Blank casing diameter 5 in Casing height above land surface TYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE	. to 35 ft., Dia 12 in., weight IAL: PVC	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft. to 0 ft. to 0 ft.	0 ft.	many feet? 1
Blank casing diameter 5 in Casing height above land surface PYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft. to 0 ft. to 0 ft. to 0 ft.	0 ft.	
Blank casing diameter 5 in Casing height above land surface FYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft.	0 ft.	
Blank casing diameter 5 in Casing height above land surface FYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft.	0 ft.	
Blank casing diameter 5 in Casing height above land surface PYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft.	0 ft.	
Blank casing diameter 5 in Casing height above land surface FYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft.	to 0 ft.	0 ft.	
Blank casing diameter 5 in Casing height above land surface PYPE OF SCREEN OR PERFORATION MATER. SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE STOUT Intervals: From 3 ft. to What is the nearest source of possiblication from well? HORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 23 ft. to From 0 ft. to LITHOLOGIC LOG	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 40 ft., Fr 0 ft., Fr	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft. FROM	to Oft. to Oft. to Oft. to Oft. to Oft. TO	O ft. How	
Blank casing diameter 5 in Casing height above land surface FYPE OF SCREEN OR PERFORATION MATER SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 3 ft. to What is the nearest source of possil Direction from well? MORTHEAST FROM	to 35 ft., Dia 12 in., weight IAL: PVC SAW CUT From 35 ft. to From 0 ft. to From 0 ft. to From 0 ft. to LITHOLOGIC LOG CATION: This water wand this record is to	in. to 0 lbs/ft. 40 ft., Fr 0 ft., Fr 0 ft., Fr 0 ft. to SPTIC TANK	Oft., I Wall thicks OR Oft. ON Oft. ON Oft. ON Oft. FROM	to 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft. To 0 ft.	O ft. How PLUGGING IN and was f. Kansas	TERVALS