

Form WWC-5

Division of Water Resources; App. No.

FD-37

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number	
County: Edwards		SE ¼ SE ¼ SE ¼	18		T 26 S	R 20 E W	
Distance and direction from nearest town or city street address of well if located within city? From Wright , appx			Global Positioning System (decimal degrees, min. of 4 digits)				
			Latitude: 37.7785				
			Longitude: 099.5439				
			Elevation: 2264				
			Datum:				
			Data Collection Method:				
2 WATER WELL OWNER: Leroy Wetzel							
RR#, St. Address, Box # : 2167 20 th Ave							
City, State, ZIP Code : Offerle, Ks 67863							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 87 ft.				
X N NW NE W SW SE S X			Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr Pump test data: Well water was 66 ft. after 4 hours pumping 473 gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No x ; If yes, mo/day/yrs Sample was submitted Water Well Disinfected? Yes x No				
5 TYPE OF CASING USED:			CASING JOINTS: Glued Clamped				
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)			Welded X				
2 PVC 4 ABS 7 Fiberglass			Threaded				
Blank casing diameter 16 in. to 87 ft., Dia			in. to ft., Dia in. to ft.				
Casing height above land surface 12 in., Weight 42 lbs./ft.			Wall thickness or gauge No. .250				
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Guaze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 27 ft. to 47 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 20 ft. to 87 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below)							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well							
Direction from well? North East How many feet? 271							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0 2 Top soil							
2 5 Fine sand							
5 30 Sand fine to med coarse w/gravel							
30 43 Sand fine to med coarse w/clay stringers							
43 55 Gray clay							
55 60 Fine sand							
60 67 Sand fine to med coarse w/rock							
67 77 Sandy clay							
77 85 Yellow soap stone							
85 100 Yellow gray soap stone							
100 140 Gray soap stone							

