WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.		
1 LOCATION OF WA	TER WELL:	Fraction		Section Number	Township No.	Range Number
County: Edwards		1/4 SE 1/4 SE		20	T 26 S	R 20 □E 🗗 W
Street/Rural Address		Global Positioning	System (GPS) is	nformation:		
from nearest town or intersection: If at owner's address, check here \square .				Latitude: (in decimal degrees)		
8 South, 1 1/4 East of Offerle				Longitude: (in decimal degrees)		
				Elevation:		·····
2 WATER WELL OV	WNER: Steve W	/otzal		Datum: WGS 8- Collection Method:	4, ∐ NAD 83, ∐] NAD 27
RR#, Street Address, Box #: 151 S Road				GPS unit (Make/Model:)		
City, State, ZIP Code : Offerle, KS 67563				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
	Onone.	1007000		Est. Accuracy:		
3 LOCATE WELL	A DEPTH OF	COMPLETED ME	. 50			
WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)						
SECTION BOX: Depth(s) Groundwater Encountered (1)						(3) ft.
	Pumn	test data: Well water	r wae	f after	hours num	ning
Pump test data: Well water wasft. after						pninggpm
W -NW - -NE - EST. YELD.JWAgpm. Well water was						ft
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well						
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well						
Was a chemical/bacteriological sample submitted to Department? \(\subseteq \text{Yes} \) No						
S If yes, mo/day/yr sample was submitted						
Water well disinfected? ✓ Yes □ No						
5 TYPE OF CASING USED: Steel V PVC Other						
CASING JOINTS: ☑ Glued ☐ Clamped ☐ Welded ☐ Threaded						
Casing diameter .5 in. to .50 ft., Diameter in. to ft., Diameter in. to ft.						
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel						
SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)						
SCREEN-PERFORATED INTERVALS: From 50 ft. to 30 ft., From ft. to ft.						
From						
GRAVEL FACK INTERVALS: From						
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)						
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well North ☐ Distance from well 150ft						
FROM TO	LITHOLOG		FROM			IGGING INTERVALS
	top soil				0 (00111) <u>01</u> 1 10 0	CONTO NATER AND
	k gravel- clean, c	oarse, loose				
47 50 Gray cl						
	· · · · · · · · · · · · · · · · · · ·					
7 CONTRACTORS OF	LANDOUNED	S CEDTIFICATION	N. This			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .12-4-12						
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 1-15-13						
under the business name of Rosencrantz-Bemis by (signature)						
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Toneka Kansas 66612-1367						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212	more, april.			Check: X Wh	ite Copy Rh	ie Copy, Pink Copy
					p,, <u></u> Dit	copy, Link copy

KSA 82a-1212