COUNTY: FORD NB	action 1/4 SV	1/4 SE		Section N	umber	Townshi	Number 8		Range Nu R 22	_
Distance and direction from nearest FROM WRIGHT = 8 MILES RAST, 1 SOUTH				f well if l	ocated wit	hin city?				
WATER WELL OWNER: RR#, St. Address, Box #: 12751 & City, State, ZIP code : SPEARVE	BARTT BOYD	67876-			rd of Agri lication N		Division	of Wat	er Resou	rces
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			RTED WELL dwater Enc	285 ountered	BLBVATION: 1.		2.	0 ft.	3.	0 ft
NA NB	WELL'S			115 ft. b Well water				on no/d		8/14/06 0 EP
	Estimate	ed Yield	40 gpm:	Well water	VAS 0	ft. afte	r 0	hours p	umping	0 gp
¥	B Bore Ho	le Diamete	er	9 in. t	o 285 ft	., and	s in.	to	Oft.	
SH SB	ABLL AV	TER TO BE	USED AS:	DOMESTIC						1
/ X3				ical sample ás submitte		to depar			disinfe	ted? Ye
Blank casing diameter 5 Casing height above land surface	in. to 285 12 in., BRIAL: PVC	ft., Dia weight			t., Dia thickness			ft.	,	•••••
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS:	in. to 285 12 in., BRIAL: PVC B: SAW CU From 2 From	ft., Dia weight T 20 ft. to 0 ft. to	in. 200 lbs 285 ft. 0 ft.	to 0 f /ft. Wall , From	thickness oft. to ft. to	or gauge 0 ft. 0 ft.				
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR	in. to 285 12 in., BRIAL: PVC B: SAW CU From 2 From	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to	200 lbs 200 lbs 285 ft. 0 ft.	to 0 f /ft. Wall , From , From , From	thickness oft. to ft. to	or gauge Oft. Oft. Oft.				
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE	in. to 285 12 in., BRIAL: PVC R: SAW CU Prom 2 Prom Prom Prom	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to From	200 lbs 285 ft. 0 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From	o ft. to ft. to ft. to	or gauge 0 ft. 0 ft. 0 ft. 0 ft.	No. 21 1	?	many fe	et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION NATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the nearest source of pos Direction from well? FROM ; TO ;	in. to 285 12 in., BRIAL: PVC E: SAW CU From 2 From From From LITHOLOGIC	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to 0 ft. to	200 lbs 285 ft. 0 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	?		et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the nearest source of pos Direction from well? FROM TO 0 20 01 TOPSOIL 32 20 40 32 TAN GLAY 3	in. to 285 12 in., BRIAL: PVC E: SAW CU From 2 From From From LITHOLOGIC TAN CLAY 6 BLUE CLAY	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to 0 ft. to	200 lbs 285 ft. 0 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the nearest source of pos Direction from well? FROM: TO : 0	in. to 285 12 in., BRIAL: PVC E: SAW CU From 2 From From From LITHOLOGIC TAN CLAY 6 BLUE CLAY 32 TAN CLAY	ft., Dia weight 7 20 ft. to 0 ft. to 20 ft. to From nation: N	285 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the mearest source of pos Direction from well? FROM TO 0	in. to 285 12 in., BRIAL: PVC R: SAW CU From 2 From From From LITHOLOGIC TAM CLAY 6 BLUE CLAY 37 FIN-COAR S	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to From nation: M	285 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the mearest source of pos Direction from well? FROM TO 0 20 01 TOPSOIL 32 20 40 32 TAM CLAY 3 40 50 36 BLUE CLAY 60 80 16 GRAY CLAY	in. to 285 12 in., BRIAL: PVC R: SAW CU From 2 From From From LITHOLOGIC TAM CLAY 6 BLUE CLAY 37 FIN-COAR S	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to From nation: M	285 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?
Blank casing diameter 5 Casing height above land surface TYPE OF SCREEN OR PERFORATION MATI SCREEN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the nearest source of pos Direction from well? FROM	in. to 285 12 in., BRIAL: PVC E: SAW CU From 2 From Prom From LITHOLOGIC TAN CLAY 6 BLUE CLAY 32 TAN CLAY 37 FIN-COAR S 67 BLUE SHALE	ft., Dia weight 7 20 ft. to 0 ft. to 20 ft. to Trom nation: N	285 ft. 0 ft. 0 ft. to	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?
Casing height above land surface TYPE OF SCREEN OR PERFORATION MATESIAN OR PERFORATION OPENINGS AR SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 0 ft. What is the nearest source of post Direction from well? FROM TO 01 TOPSOIL 32 20 40 32 TAM CLAY 3 40 60 36 BLUE CLAY 60 80 16 GRAY CLAY 100 120 36 BLUE CLAY 120 140 36 BLUE CLAY 140 140	in. to 285 12 in., BRIAL: PVC E: SAW CU From 2 From From From From Con LITHOLOGIC TAN CLAY 6 BLUE CLAY 32 TAN CLAY 37 FIN-COAR S 67 BLUE SHALE	ft., Dia weight T 20 ft. to 0 ft. to 20 ft. to From nation: N LOG	in. 200 lbs 285 ft. 0 ft. 285 ft. 0 ft. tolione	to 0 f /ft. Wall , From , From , From , From , From	O ft. to O ft. to O ft. to O ft. to Ft. to O ft. to	Oft. Oft. Oft. Oft.	No. 21 1	? t.		et?

¹⁷ CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/15/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179

This Water Well Record was completed on (mo/day/yr) 09/14/06 under the business name of JOB'S WELL SERVICE, INC.

by (signature)