WATER WELL RECORD Form WWC-5					Di	vision of Wate	r Resources App. No	).	
1 LOCATION OF WATER WELL:			Fraction				Township No.		
County: Ford			AE'A NE'/4 NE	=1/4 nE/4		20		R ŽZ □E 🗷W	
		ddress of Well Location;			l Positioning	System (GPS) in			
from nearest town or intersection: If at owner's address, check here 🔀.						Latitude: (in decimal degrees)			
					Long	Longitude: (in decimal degrees)			
,						Elevation:			
2 WATER WELL OWNER. (1) A land Maria						Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Gil Acker Man						Collection Method:  GPS unit (Make/Model:)			
RR#, Street Address, Box #: /2579 Jewell Rd. City, State, ZIP Code:					☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
Sycarville, Ks. 6787				6	Est. A	Est. Accuracy: $\square$ <3 m, $\square$ 3-5 m, $\square$ 5-15 m, $\square$ >15 m			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 330 ft.									
	H AN "X'	IN 4 DEPTH OF	COMPLETED WEL	<u>د</u> کی	<b>5</b> 0	ft.			
SECT						ft. (2) ft. (3) ft.			
	N				ft. below land surface measured on mo/day/yr				
		<b>≯</b> Pump	test data: Well water was						
			gpm. Well water wasft. after hours pumping gpm						
W			ter						
		WELL WATER	TO BE USED AS:	Public wa	ter suppl	у 🗆 Се	othermal   I	njection well	
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well									
was a chemical/bacteriological sample submitted to Department? Yes Ar No  S If yes, mo/day/yr sample was submitted									
mile  Water well disinfected? X Yes \( \sum \) No									
Water wert distincted. At 1 cs 1 140									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter									
Casing height above land surface									
Steel Stainless Steel VPVC Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
Louvered shutter									
SCREEN-PERFORATED INTERVALS: From 270 ft. to 530 ft., From ft. to ft.									
From									
From									
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other									
Grout In		From ft. to	ft From	120	ft to	130 ft	From	ft to ft	
			• •		10. 00 11.		110111		
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)									
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well									
		nt sewer lines 🔲 Seepage p	oit	Fertilizer s		☐ Oil well/ga			
		well Eacst				ell		GCDIG DIEDETTIC	
FROM	TO	LITHOLOG	IC LOG	FROM	TO	_	A	GGING INTERVALS	
0	12	70.pszil		/30	148	Sandst	PVC		
a Z	12	Tan clay		148	720				
12	44	white rock		220	330	SANDS	tone + Shall	e layers	
44	42	Yellow clay			-				
41 51	52	Red clay							
57	75	Tan chay	<u> </u>						
72	27	limestone + Tax	CIAY						
27	95	Tan clay	•						
95	97	whiterock							
77 / 30 Shale									
under my jurisdiction and was completed on (mo/day/year)									
Kansas Water Well Contractor's License No									
under the business name of Santzen Water Well by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the carect answers. Send three copies									
(white, blu	ue, pink) to	Kansas Department of Health	and Environment, Bureau	of Water, Geo	logy Section	on, 1000 SW Ja	ckson St., Suite 420,	Горека, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.  KSA 82a-1212									
MOM 02a	-1212								