CORRECTION(S) TO WATER WELL RECORD (WWC-5)

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

Distance and direction from mearest town or city street address of well if located within city? FROM MRIGHT E. QW-YEWELL TO RD. 121 SOUTH 1 NILE EAST 3/4 MATER MELL OWNER: VOGEL, ALAM MRRS, St. Address, Box 8: 1217Z KETTLE RD. Board of Agriculture, Division of Water Resources Application Mumber: LOCATE MELL'S LOCATION WITH
MATER WELL OWNER: WARS, St. Address, Box \$: 12172 KETTLE RD. Board of Agriculture, Division of Mater Resources City, State, ZIP code : MRIGHT, KS 67882- LOCATE MELL'S LOCATION WITH
Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 WELL'S STATIC MATER LEVEL 118 ft. below land surface measured on mo/day/yr 08/27/ Pump testdata: Well water was 0 ft. after 0 hours pumping 0 WELL STATIC MATER LEVEL 118 ft. below land surface measured on mo/day/yr 08/27/ Pump testdata: Well water was 0 ft. after 0 hours pumping 0 WELL WATER TO 8E USED AS: DOMESTIC WELL MATER TO 8E USED AS: DOMESTIC If yes, mo/day/yr sample was submitted to department? No; If yes, mo/day/yr sample was submitted water well disinfected? TYPE 0F BLANK CASING USED: CERTA LDC CASIN CASING JOINTS: CERTA-LDC Blank casing diameter 5 in. to 445 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 17 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAM CUT SCREEN PERFORATED INTERVALS: From 340 ft. to 440 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 25 ft. to 445 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. How many feet?
Pump testdata: Well water was 0 ft. after 0 hours pumping 0 Estimated Yield 50 gpm: Well water was 0 ft. after 0 hours pumping 0 W
Estimated Yield SO gpm: Well water was 0 ft. after 0 hours pumping 0 M
MELL MATER TO BE USED AS: DOMESTIC MELL MATER TO BE USED AS: DOMESTIC MELL MATER TO BE USED AS: DOMESTIC Mas a chemical/bacteriological sample submitted to department? No; If yes, mo/day/yr sample was submitted Mater well disinfected? Mas a chemical/bacteriological sample submitted Mater well disinfected? Mater well di
Was a chemical/bacteriological sample submitted to department? No; If yes, mo/day/yr sample was submitted Water well disinfected? YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CERTA-LOC Blank casing diameter 5 in. to 445 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 17 ITYPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAM CUT SCREEN PERFORATED INTERVALS: From 340 ft. to 440 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 25 ft. to 445 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft. From 2 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft. From 2 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft. From 2 ft. to 0 ft., From 0 ft. to 0 ft. From 1 ft. to 0 ft. From 2 ft. to 0 ft. From 3 ft. to 0 ft. From 3 ft. to 0 ft. From 3 ft. to 0 ft. From 4 ft. to 0 ft. From 5 ft. to 0 ft. From 6 ft. to 0 ft. From 7 ft. to 0 ft. From 8 ft. to 0 ft. From 9 ft.
YPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CERTA-LOC clank casing diameter 5 in. to 445 ft., Dia in. to 0 ft., Dia in. to 0 ft. assing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 17 YPE OF SCREEN OR PERFORATION MATERIAL: PVC CREEN OR PERFORATION OPENINGS ARE: SAM CUT CREEN PERFORATED INTERVALS: From 340 ft. to 440 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 445 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. HOW many feet?
Stank casing diameter 5 in. to 445 ft., Dia in. to 0 ft., Dia in. to 0 ft. Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 17 IMPE OF SCREEN OR PERFORATION MATERIAL: PVC SCREEN OR PERFORATION OPENINGS ARE: SAM CUT SCREEN PERFORATED INTERVALS: From 340 ft. to 440 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. GRAVEL PACK INTERVALS: From 25 ft. to 445 ft., From 0 ft. to 0 ft. From 0 ft. to 0 ft., From 0 ft. to 0 ft. SROUT MATERIAL BENTOMITE Grout Intervals: From 5 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: ABANDONED WELL Direction from well? SOUTH How many feet?
From 0 ft. to 0 ft., From 0 ft. to 0 ft. GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: ABANDONED WELL Direction from well? SOUTH How many feet?
Grout Intervals: From 5 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft. What is the nearest source of possible contamination: ABANDONED WELL Direction from well? SOUTH How many feet?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS O 20 01 TOPSOIL 05 CLAY
20 ; 40 ; 32 TAN CLAY 24 THINROCLAYER
20 40 32 TAN CLAY 24 THINROCLAYER 40 60 32 TAN CLAY 05 CLAY 24 THINROCLAYER
20
20
20 40 32 TAN CLAY 24 THINROCLAYER 40 60 32 TAN CLAY 05 CLAY 24 THINROCLAYER 60 80 36 BLUE CLAY 16 GRAY CLAY 24 THINROCLAYER 80 140 16 GRAY CLAY 08 ROCK LAYERS 140 160 16 GRAY CLAY 29 SANDSTONE
20
20
, , , , , , , , , , , , , , , , , , , ,

under the business name of JOE'S WELL SERVICE, INC. by (signature) Judith Cuck

- 1	CAL		nued	١
·	LUI	1 L 1	HUEU	

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION COUNTY:	OF WATER WELL Ford	: Fraction SE 1/4 SW			Township Number T 21 S	Range Number
		VOGEL, ALAN 1: 12172 KETTLE RD. : WRIGHT, KS 6788	12-	Board of Agric Application Nu	ulture, Division of (mber:	Water Resources
FROM 320 420	420 16	LITHOLOGIC GRAY CLAY 29 SANDSTONE SANDSTONE	FOE			
					7	
1	 					
1 1 1 1 1	 					
1 1 1 1 1 1						

¹⁷ CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/29/09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179

This Water Well Record was completed on (mo/day/yr) 12/15/09 under the business name of JOE'S WELL SERVICE, INC.

by (signature)