				WELL RECORD	Form WWC-5	KSA 82				<del></del> i	
	ON OF WAT Ford	TER WELL:	Fraction	01/2 0	1	tion Number			Range Num		
County:				S1/2 1/4 S dress of well if locate	SW 1/4	20	Т 26	Ş	R 24	E(W/	
Distance a	na airection			North of Do		_					
			County La		age City	<u> </u>					
_	WELL OW		re Star 1							. 1	
,	Address, Box	D - 1		. 67901		MEA		•	ivision of Water F	lesources	
	ZIP Code		City, K	3. 6/801	210	MW	13D Application				
J LOCATE	MELL'S LO	1 DAV.		MPLETED WELL						. 4	
	0201101	1 I D	epth(s) Groundw	rater Encountered	1	ft.	2	ft. 3.		ft.	
Ī	!	!   w		WATER LEVEL $11\%$							
	- NW	NE	•	test data: Well wat				•			
1	1	, E:		gpm: Well wat							
₩ W	1	l B	ore Hole Diamet	er8in. to	210		and	in.	to	ft.	
₹ "	!	!   ' w	ELL WATER TO	BE USED AS:	5 Public water		8 Air conditioning	•	njection well		
ī L	- SW	SE	1 Domestic	3 Feedlot					Other (Specify bel		
	- <b>*</b> - 1	ī	2 Irrigation	4 Industrial						1	
↓ L		ı	/as a chemical/ba	acteriological sample	submitted to De	•		-		was sub-	
	5		itted			W	ater Well Disinfec	ted? Yes	No X		
5 TYPE C	F BLANK C	CASING USED:		5 Wrought iron	8 Concre	te tile	CASING J	OINTS: Glued	Clamped		
1 Ste	el	3 RMP (SR)		6 Asbestos-Cement	9 Other (	specify belo	ow)		ed		
2 <u>PV</u>		4 ABS		7 Fiberglass					ded <sup>X</sup>		
Blank casir	ng diameter	in	. to 200 .	ft., Dia	$\ldots$ . in. to		ft., Dia	i	n. to	ft.	
Casing hei	ght above la	and surface	30	n., weight	2.071.	Ibs	./ft. Wall thickness	s or gauge No	b• 2.3 /		
TYPE OF	SCREEN O	R PERFORATION I	MATERIAL:		7 PV	<u> </u>	10 As	sbestos-ceme	nt	-	
1 Ste	el	3 Stainless s	teel	5 Fiberglass	8 RM	P (SR)	11 0	ther (specify)			
2 Bra	ISS	4 Galvanized	l steel	6 Concrete tile	9 ABS	S	12 N	one used (op	en hole)		
SCREEN C	OR PERFOR	RATION OPENINGS	S ARE:	5 Gau	zed wrapped		8 Saw cut		11 None (open h	nole)	
1 Co	ntinuous slo	t 3 Mill	slot	6 Wire	wrapped		9 Drilled holes	5			
2 Lou	vered shutt	er 4 Key		7 Torc							
SCREEN-F	PERFORATE	ED INTERVALS:	From	$200\ldots$ . ft. to .	210	ft., Fro	om	ft. to	). <i>.</i>	ft.	
				ft. to .							
G	RAVEL PA	CK INTERVALS:	From	198 ft. to .	210	ft., Fro	om	ft. to	) <sup>.</sup>	ft.	
			From	ft. to		ft., Fro	om	ft. to	)	ft.	
6 GROUT	MATERIAL	: 1 Neat cer	ment 2	Cement grout	3 Bento	nite 4	Other			,	
Grout Inter	vals: From	n 0 ft.	to 192	ft., From	9.2 ft. 1	to 1 9	6 ft., From .		. ft. to	ft.	
What is the	e nearest so	ource of possible co	entamination:			10 Live	stock pens	14 At	andoned water w	ell	
1 Se	ptic tank	4 Lateral	lines	7 Pit privy		11 Fuel	storage	15 Oi	well/Gas well	-	
2 Se	wer lines	5 Cess po	ool	8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)				
3 Wa	itertight sew	er lines 6 Seepag	e pit	9 Feedyard		13 Inse	cticide storage	Landf	<del>;</del>		
Direction fr					<b>.</b>	How ma	any feet?				
FROM	то		LITHOLOGIC L	OG	FROM	то		PLUGGING IN			
0	2	Surface			120	151	Fine to N		nd w/a Fe	w Fin	
2	11	Loess							Layers	-	
11	39	Clay & Ca	aliche		151		Sandy Cla				
39	40	Caliche 8	Clay		159		Fine Sand				
40	47	Clay & Ca			171				nd w/Clay		
47	48	Hard Cali	che		180				vel w/a F		
48	54			lay & S.Sa				Clay	Layers		
54	58	Cemented			191	210	Tight Med		w/Clay S	trks.	
58	62			ented Strks		211	Shale				
62	65	Cemented									
65	80	Sandy Cla		-							
80	90	Sandy Cla	-							. 12.0	
90	100	Sandy Cla	y w/a Fe	w Fine San	d Strks.						
100	118			Sand Strk							
118	120	Sandy Cla	_								
1		_	_	N: This water well w	uge (1) construc	etad (2) res	constructed or (2)	olugged use	er my juriediction	and was	
	on (mo/day/		-96	AT. THIS WATER WELL					er my jurisdiction wledge and belief		
		s License No	554	This Motor 1			ord is true to the t on (mo/day/yr)		-09-96	. Nalisas	
	contractor ousiness na	5.7 · · C · ·		Well, Inc	ven necord was	-			tuo		
		110 07				by (signa			$\overline{\lambda}$		
				<u>RMLY</u> and <u>PRINT</u> clearly. P 0001. Telephone: 913-296						unent	