

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford 029		SE 1/4 SE 1/4 SE 1/4	13	T 26 S	R 24 EW
Distance and direction from nearest town or city street address of well if located within city? In the town of Wright, Kansas 67882 (new house)					
2 WATER WELL OWNER: Maurice Stine Stine					
RR#, St. Address, Box # : 112 N. Wilson			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Ulysses, Kansas 67880			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 110 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 3-30-88			
		Pump test data: Well water was 90 ft. after 1 hours pumping 1.0 gpm			
		Est. Yield 10 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 110 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 90 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 110 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 20 3 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	butine	10 Livestock pens
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
				13 Insecticide storage	16 Other (specify below)
Direction from well? south		How many feet? 30 ft.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	49	topsoil & clay			
49	60	caliche			
60	75	caliche (hard)			
75	90	caliche & soft clay			
90	100	soft sandy clay			
100	105	rocks & sand			
105	110	yellow to white clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-30-88 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 130		This Water Well Record was completed on (mo/day/yr) 4-22-88			
under the business name of Leo Knoefler Drilling		by (signature) <i>Leo Knoefler</i>			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					