


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 15 Township Number T 26 S Range Number R 24 E **(W)**
 County: Ford

Distance and direction from nearest town or city street address of well if located within city?
2 miles West of wright, Kansas

2 WATER WELL OWNER: Farmland Industries
 RR#, St. Address, Box #: HyWay 50 E. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Dodge City, Kansas 67801 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION: slope
 Depth(s) Groundwater Encountered 1. 75 ft. 2. 75 ft. 3. 75 ft.
 WELL'S STATIC WATER LEVEL: 62 ft. below land surface measured on mo/day/yr 10-8-83
 Pump test data: Well water was 82 ft. after 82 hours pumping 82 gpm
 Est. Yield 9 gpm; Well water was 82 ft. after 82 hours pumping 82 gpm
 Bore Hole Diameter: 9 3/4 in. to 125 ft., and 125 in. to 125 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded X
 Blank casing diameter 5 in. to 125 ft., Dia 5 in. to 125 ft., Dia 5 in. to 125 ft.
 Casing height above land surface 12 in., weight 3 lbs./ft. Wall thickness or gauge No. SDR 21
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify) X
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) X
 SCREEN-PERFORATED INTERVALS: From 95 ft. to 125 ft., From 95 ft. to 125 ft., From 95 ft. to 125 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 125 ft., From 13 ft. to 125 ft., From 13 ft. to 125 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other X
 Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) none
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Surface			
3	30	Brown clay			
30	75	Caleche clay and rock stringers			
75	102	Brown sandy clay			
102	125	50% fine sand with clay			
125	140	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-8-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 302 This Water Well Record was completed on (mo/day/yr) 5-10-87 under the business name of Hodde Drilling Co. by (signature) [Signature]