			WATER	WELL RECORD	Form WWC-	5 KSA 8	2a-1212	\subset	5DV	06	, 1
1 LOCATI	ON OF WAT	ER WELL:	Fraction		-	ction Numbe		Number	Ran	ge Num	ber
County:				NE ¼ NE		22	т 26	S		4	₽ ∕W
		from nearest town of		dress of well if locate			<u></u>				
21 M	. west	of Wri#ht	. Kansas	s on Hwy 50)						
2 WATER	R WELL OW	NER: Farmlan	d Indus	tries Inc.	<u></u>						
DD# 81	Address Bo	# Box 133	37				Poord of	Agricultura	Division of	Motor F	3
			litv. Ke	nsas 67801				Agriculture,	Division of	water F	1esources
	, ZIP Code					· · · · · · · · · · · · · · · · · · ·		on Number:			-
J LOCATI	IN SECTION	DCATION WITH 4	DEPTH OF CO	MPLETED WELL.	LO.2	ft.ELEV	/ATION: . Blo]	pe			
/// /_	11 020110	1 De		ater Encountered							
.ī	!	. x W		WATER LEVEL38							
	NW	· 1	Pump	test data: Well wat	er was	ft.	after	hours p	umping		gpm
	1444	Es		gpm: Well wat							
•	i	•		er9,in. to							
. ₩ F	1			BE USED AS:	5 Public wat				Injection v		
- I	ı	i	1 Domestic				9 Dewatering	-	•		ow)
-	SW	SE	2 Irrigation	4 Industrial			10 Observation v			-	-
1	!	w.	•	acteriological sample							
<u>i</u> L			as a chemical/bi	acteriological sample	Submitted to L		-	-			was sub
EL TYPE	OF BLANK C	ASING USED:	RIBU	F Manualitina	0.0		Vater Well Disinfec				
				5 Wrought iron							
1 Ste		3 RMP (SR)		6 Asbestos-Cement			•		ded		
2 P)	/C	54 ABS	90	7 Fiberglass			• • • • • • • • • • • • • • • • • • • •		aded		
Blank casi	ing diameter	5in	to ?	ft., Dia	in. to)	ft., Dia		in. to	·····	ft.
Casing he	ight above la	ınd surface	.	in., weight \dots 3		lb:	s./ft. Wall thickness	s or gauge N	10. ・・・設す	K 5T	*
TYPE OF	SCREEN O	R PERFORATION M	MATERIAL:		7 P\	<u>/C</u>	10 As	sbestos-cem	ent		
1 Ste	eel	3 Stainless st	teel	5 Fiberglass	8 RI	MP (SR)	11 0	ther (specify)	. <i></i>	
2 Br	ass	4 Galvanized	steel	6 Concrete tile				one used (o			
SCREEN	OR PERFOR	RATION OPENINGS	ARE:	5 Gauz	zed wrapped		8 Saw cut		11 None	(open h	nole)
1 Co	ontinuous slo	t 3 Mills	slot	6 Wire	wrapped		9 Drilled holes			• •	·
2 Lo	uvered shutt	er 4 Kev i	punched	7 Torc	h cut		10 Other (spec	ifv)			
		D INTERVALS:	From 90	ft. to .	102	ft F	rom	,, 	to		
CONTENT	0.0			ft. to .							
,	CDAVEL DA	CK INTERVALS:		3 ft. to .							
,	GRAVEL PA	ON INTERVALS.	_								
0.00011	TAATEDIAL		From	ft. to	0.5				· ·		ft.
	T MATERIAL		nent 12 <u>-</u> 2	Cement grout	3 Bent	onite	4 Other				
Grout Inte				ft., From	n t.						
		urce of possible cor						14 /			rell
1 Septic tank 4 Latera						11 Fuel st		=		Oil well/Gas well	
2 Sewer lines 5 Cess p			ool	8 Sewage lagoo		on 12 Fertilizer storage		16 Other (specify below)			N)
3 W	atertight sew	er lines 6 Seepage	e pit	9 Feedyard		13 Ins	ecticide storage	n oi	1e	<i>.</i>	
Direction f	from well?					How m	any feet?				
FROM	то		LITHOLOGIC L	OG	FROM	то		LITHOLO	GIC LOG		
0	3	Surface									
3.	28	Brown dry	r clav		1						
28	30	Sticky br		v							
30	45	Caleche c		,							
45	85	Brown cla									
85	102	Fine sand									
				1 y		 					
102	105	Brown cla	1y			<u> </u>					
						 	 	 .			
						1					
				· · · · · · · · · · · · · · · · · · ·							
									<u> </u>		
						1					
		· · · · · · · · · · · · · · · · · · ·	<u> </u>								
7 CONT	DACTODIO (AD I ANDOMASICOS	CEDTIEICATIC	Mi. This water		intend (A)	Annahu			المالمة	
T CON!	HAUTUR'S (M LANDOWNER'S	CERTIFICATION (CATION CATION C	N: This water well v							
completed	on (mo/day/	year) 6-23-8	(-)			and this re	cord is true to the t	pest of my ki	nowledge a	nd belief	r. Kansas
water Wel	II Contractor'	s License No. 30	? (-	This Water V	veli Record w	as complete	d on (mo/day/yr)	. ユ∠∹⊥0-	-02		
under the			Th	- A-			-			//	
		me of Hodde	Drillin,	g Co.		by (sigr	nature) Will	lû_	The	the	
INSTRUC	TIONS: Use	vpewriter or ball poi	Drillin	CO. <i>PRESS FIRMLY</i> are pent, Division of Enviro	nd <i>PRINT</i> clear	by (sign	l in blanks underlin	ne or circle	le correct a	nswers.	Send top