PPROX. 1/2 MILE EAST OF DODGE CIT 	IS BEEF						
R#, St. Address, Box # : 2000 E. ity, State, ZIP code : DODGE (rd of Agri lication N	culture, Di umber:	vision of	Water Re	sources
	: 4 DEPTH OF COMPLETED W Depth(s) Groundwater				2. 0	ft. 3	. 0
	WELL'S STATIC WATER LE Pump testdat	EVEL 120 ft.b ta: Well water				mo/day/yr rs pumpin	
	Estimated Yield 0	gpm: Well water	was O	ft. after	0 hou	rs pu m pin	g 0
W	E : Bore Hole Diameter	in. t	o 0 ft	., and	in. to	0 ft.	
	WELL WATER WAS: 10 MOI	NITORING					
	: . Was a chemical/bacteri	inlanical samale	submitted	to departm	ent? No :		
		ple was submitte NTS: GLUED io. to 0 f	d t Dia	in. to	Water w	ell disin	fected?
1 1 1	I If yes, mo/day/yr sam CASING JOIN in. to 327 ft., Dia -36 in., weight (ERIAL: 07 PVC E: UNKNOWN	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From	t., Dia thickness	in. to or gauge No	Water w	ell disin	fected?
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARE	CASING JOIN CASIN	ple was submitte NTS: GLUED in. to O f O lbs/ft. Wall O ft., From O ft., From O ft., From	t., Dia thickness Oft. to Oft. to Oft. to	in. to or gauge No O ft. O ft. O ft.	Water w	ell disin	fected?
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARI CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS:	CASING JOIN CASIN	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From	t., Dia thickness oft. to oft. to	in. to or gauge No O ft. O ft.	Water w	ell disin	
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARI CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of pos	CASING JOIN CASIN	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From Oft., From Oft., From Oft., From	t., Dia thickness Oft. to Oft. to Oft. to	in. to or gauge No O ft. O ft. O ft. O ft.	Water w 0 ft	ell disin	
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARI CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of positivection from well?	CASING JOIN CASIN	ple was submitte NTS: GLUED in. to O f O lbs/ft. Wall O ft., From O ft., From O ft., From t. to O ft. BSERVED	t., Dia thickness Oft. to Oft. to Oft. to Oft. to	in. to or gauge No Oft. Oft. Oft. Oft. Oft.	Water w O ft O ft.	ell disin	feet?
PE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface of perforation material or perforation openings are creen or perforation openings are creen perforated intervals: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of positivection from well?	CASING JOIN CASING JOIN In. to 327 ft., Dia -36 in., weight ERIAL: 07 PVC UNKNOWN From Oft. to	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From t. to Oft. BSERVED FROM O	t., Dia thickness Oft. to Oft. to Oft. to Oft. to	in. to or gauge No Oft. Oft. Oft. Oft. Oft. I BACKFILL	Water w O ft O ft.	ell disin	feet?
PE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface PPE OF SCREEN OR PERFORATION MATERIAL OF CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of positivection from well?	CASING JOIN CASING JOIN In. to 327 ft., Dia -36 in., weight ERIAL: 07 PVC UNKNOWN From Oft. to	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From t. to Oft. BSERVED FROM O 1 3 120	t., Dia thickness Oft. to Oft	in. to or gauge No Oft. Oft. Oft. Oft. Oft. Common to	Water w O ft O ft.	ell disin	feet?
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARI CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of positicection from well?	CASING JOIN CASING JOIN In. to 327 ft., Dia -36 in., weight ERIAL: 07 PVC UNKNOWN From Oft. to	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From t. to Oft. BSERVED FROM O 1 3 120	t., Dia thickness Oft. to Oft	in. to or gauge No Oft. Oft. Oft. Oft. Comment of the comment of	Water w O ft O ft.	ell disin	feet?
YPE OF BLANK CASING USED: 02 PVC lank casing diameter 5 asing height above land surface YPE OF SCREEN OR PERFORATION MATE CREEN OR PERFORATION OPENINGS ARI CREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: ROUT MATERIAL 02 CEMENT GROUT rout Intervals: From 0 ft. hat is the nearest source of positrection from well?	CASING JOIN CASING JOIN In. to 327 ft., Dia -36 in., weight ERIAL: 07 PVC UNKNOWN From Oft. to	ple was submitte NTS: GLUED in. to Of Olbs/ft. Wall Oft., From Oft., From Oft., From t. to Oft. BSERVED FROM O 1 3 120 0	t., Dia thickness Oft. to Oft	in. to or gauge No Oft. Oft. Oft. Oft. Oft. SAND I	Water w O ft O ft.	ell disin	feet?

water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 02/08/93
under the business name of HENKLE DRILLING & SUPPLY by (signature) by the contract of the supply of the contract of the supply of the contract of the supply of the sup