	WATER WELL RECORD	Form WWC-5	KSA 82a-	1212 ID No.		<u> </u>
LOCATION OF WATER WELL:	Fraction 5	12 1/2 SE 1/4	Sec	tion Number	Township Number	Range Number
Distance and direction from neares	t town or city street addre	ess of well if located w	vithin city?		cityles	
2 WATER WELL OWNER: HITC	hin bost (ruch	LITON .	Ulivi.	Douge	417/27	
RR#, St. Address, Box #	: Toms kindsva	ter "			Board of Agriculture Application Number	re, Division of Water Resources er:
3 LOCATE WELL'S LOCATION WI			85.0.	ft. ELEVAT	ION:	3
AN "X" IN SECTION BOX:	Depth(s) Groundwa	ter Encountered 1		ft . :	2	ft. 3 ft.
N	WELL'S STATIC WA	TER LEVEL	 ft. belo	w land surface	measured on mo/day/yı	r
1 / 1	Est. Yield	gpm: Well water	was was	ft. af	terhou	irs pumpinggpri
NW NE	WELL WATER TO E	BE USED AS: 5 P	ublic water s	supply	8 Air conditioning 1	11 Injection well
w : 1	1 Domestic E 2 Irrigation		il field water		9 Dewatering	Other (Specify below)
**	2 mgalon	4 modelna 7 B	omestic (ian	in a garden, i	o workoning wen	
sw se - a	Was a chemical/bac	eteriological sample s	ubmitted to [Denartment? Ye	es No X : If ve	es, mo/day/yrs sam ple w as sub
7	mitted	teriological sample s	abilitied to t		ter Well Disinfected? Yes	
<u> </u>						
5 TYPE OF BLANK CASING US	ED: 5 \	Vrought iron	8 Concre	ete tile	CASING JOINTS: (Glued Clamped
1 Steel 3 RMF	P (SR) 6 A	Asbestos-Cement	9 Other (specify below)	\	Welded
PVC 4 ABS		iberglass				ThreadedX
Blank casing diameter	- 4 1 2	ft., Dia نمانداند	•••••	in. to	ft., Dia bs./ft. Wall thickness or g	in to the fit
Casing height above land surface. TYPE OF SCREEN OR PERFORA		in., weight			os./π. waii thickness or g -10 Asbestos	
		Fiberglass		IP (SR)		ecify)
		Concrete tile	9 AB		12 None used	• .
SCREEN OR PERFORATION OPE	ENINGS ARE:	5 Guaze	d wrapped		8 Saw cut	11 None (open hole)
	3 Mill slot	6 Wire w			9 Drilled holes	
	4 Key punched	7 Torch				ft
SCREEN-PERFORATED INTERVA	ALS: From	. ft. to	22	ft., From		ft. toft
GRAVEL PACK INTERV	ALS: From	3 ft. to	<i>5</i> 5	π., From ft From		ft. toft ft. toft
	From	ft. to		ft., From	1	ft. toft
6 GROUT MATERIAL: 1	Neat cement 2	2 Cement grout	3 Bent	0000 4	Othor	
Grout Intervals: From	ft to 63	ft From	5 Delli	2	ft From	ft. toft
What is the nearest source of poss	sible contamination:	10, 1 10,11		10 Livesto	ck pens	14 Abandoned water well
1 Septic tank 4 L	_ateral lines	7 Pit privy		11 Fuel st	•	15 Oil well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		6 Other (specify below)
3 Watertight sewer lines 6 S	9 Feedyard		13 Insection	cide storage	ust Site	
Direction from well?				How many	feet?	
FROM TO	LITHOLOGIC LO	G	FROM	то	PLUGGIN	G INTERVALS
0 0.5 Hisphal	1	<i>1</i>				
0.5 14 Sand,	dry, tine grain	e o [,				
14 2019 Sond, 1	lry, vory time grait					
23 Siltsana	l, dry, very fine g	1	6 0 1	*/-		
33 Mol 3 trevely s	dry fine to a	ukr, 4 1/2" pietes gra	rite, quaite			
70 85 Silti	SOUND VENIER	e to medium				
70 00 0110	nined	Cionidiani				
3					VORWIZ	
					-0.000	
7						
7 CONTRACTOR'S OR LANDOV	VNER'S CERTIFICATION					
completed on (mo/day/year)	17/07					w knowledge and belief. Kansas
Water Well Contractor's Licence No under the business name of	277 II	This Water V	Vell Record			12120104
	anco executy	Mins, Inc			ignature)	m c & min
INSTRUCTIONS: Use typewriter or ball po and Environment, Bureau of Water, Geolog						
records. Fee of \$5.00 for each constructed	well.					