OCATION OF WATER WELL: COUNTY: 029 FORD	="		; Secti 1/4 ; 28				=	
Distance and direction from APPROX. 2 MILES EAST, 1/2				if located wi				
WATER WELL OWNER: RR#, St. Address, Box # :		RD INC.		Board of Agr	riculture, D	ivision of	Water Re	sources
City, State, ZIP code :	DODGE CITY, KS	67801-0115	5	Application	Number: 41,	365		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			ETED WELL 425 dwater Encounter			2. 0	ft. 3	. 0 f
\	HE LX		TER LEVEL 195 estdata: Well w					
1 1 1		timated Yield	200 gpm: Well	water was	0 ft. after	0 hou	rs pumpin	g 0 g
	E Bo	re Hole Diamete	er 18.5	in. to 425	ft., and	in. to	0 ft.	
: SW S		LL WATER TO BE	USED AS: 03 FEE	DLOT				ţ.
1 1 1	; ; Wa	s a chemical/ba yes, mo/day/yr	acteriological s	ample submitte	ed to depart	ment? No ; Water w	ell disin	fected? \
YPE OF BLANK CASING USED: lank casing diameter asing height above land s YPE OF SCREEN OR PERFORAT	 02 PVC 10 in. to urface 12 in ION MATERIAL: 0	CASING 425 ft., Dia ., weight 7 PVC	G JOINTS: GLUED	0 ft., Dia	in. t	 o 0 ft		
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0	CASING 425 ft., Dia ., weight 17 PVC 13 MILL SLOT Im 345 ft. to	G JOINTS: GLUED	O ft., Dia Wall thickness O ft. to O ft. to	in. t s or gauge N O ft. O ft.	 o 0 ft		
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0	CASING 425 ft., Dia 1., weight 17 PVC 13 MILL SLOT 18 345 ft. to 19 0 ft. to 19 25 ft. to	6 JOINTS: GLUED in. to 11 lbs/ft. 425 ft., From 0 ft., From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to	in. t s or gauge N O ft. O ft. O ft.	 o 0 ft		
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL GROUT MATERIAL 03 BENTO GROUT Intervals: From	02 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0 Fro Fro Fro NITE 3 ft. to 25	CASING 425 ft., Dia ., weight 17 PVC 13 MILL SLOT 18 345 ft. to 19 0 ft. to 19 230 ft. to 19 11 ft., From	6 JOINTS: GLUED in. to 11 lbs/ft. 425 ft., From 0 ft., From 220 ft., From 425 ft., From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to	in. t s or gauge N O ft. O ft. O ft. O ft.	0 ft.		
TYPE OF BLANK CASING USED: Clank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORATION OPEN CORREEN OR PERFORATION OPEN CORREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GROUT MATERIAL O3 BENTO COROUT Intervals: From Chat is the nearest source Coroution from well?	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0 Fro Fro Fro NITE 3 ft. to 25 of possible co	CASING 425 ft., Dia 1., weight 7 PVC 13 MILL SLOT 16 345 ft. to 16 0 ft. to 17 25 ft. to 18 230 ft. to 19 11 12 12 12 12 12 12 12 12 12 12 12 12	G JOINTS: GLUED in. to 11 lbs/ft. 425 ft., From 0 ft., From 220 ft., From 425 ft., From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to O ft. to	in. to or gauge N Oft. Oft. Oft. Oft.	0 ft.	How many	
YPE OF BLANK CASING USED: Slank casing diameter Casing height above land s YPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN GCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GROUT MATERIAL OS BENTO Grout Intervals: From What is the nearest source Direction from well? FROM TO O	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0 S: Fro Fro S: Fro NITE 5 ft. to 25 of possible co	CASING 425 ft., Dia 1., weight 7 PVC 13 MILL SLOT 14 0 ft. to 15 ft. to 16 25 ft. to 17 ft., From 18 10 ft., From 19 11 ft., From 10 11 ft., F	G JOINTS: GLUED in. to 11 lbs/ft. 425 ft., From 0 ft., From 220 ft., From 425 ft., From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to	in. to or gauge N Oft. Oft. Oft. Oft.	0 ft.		
TYPE OF BLANK CASING USED: Clank casing diameter Casing height above land s CYPE OF SCREEN OR PERFORAT CORREEN OR PERFORATION OPEN CORREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL GROUT MATERIAL 03 BENTO Crout Intervals: From What is the nearest source Correction from well? FROM TO O 2 O2 SIL 2 23 O4 SAN 23 42 O4 SAN 42 54 O4 SAN 42 54 O4 SAN 43 54 O4 SAN 46 54 O4 SAN	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0 S: Fro Fro S: Fro NITE 5 ft. to 25 of possible co LITHOL T IDY CLAY 31 CALI IDY CLAY IESTONE 04 SANDY	CASING 425 ft., Dia 1., weight 17 PVC 13 MILL SLOT 16 0 ft. to 16 0 ft. to 17 0 ft. to 18 18 18 18 18 18 18 18 18 18 18 18 18 1	G JOINTS: GLUED in. to 11 lbs/ft. 425 ft., From 0 ft., From 220 ft., From 425 ft., From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to O ft. to	in. to or gauge N Oft. Oft. Oft. Oft.	0 ft.	How many	
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land s TYPE OF SCREEN OR PERFORAT SCREEN OR PERFORATION OPEN SCREEN PERFORATED INTERVAL GRAVEL PACK INTERVAL GRAVEL PACK INTERVAL GROUT MATERIAL O3 BENTO Grout Intervals: From What is the nearest source Direction from well? FROM : TO : 0 : 2 : 02 SIL 2 : 23 : 04 SAN 23 : 42 : 04 SAN 42 : 54 : 04 SAN 42 : 54 : 04 SAN 42 : 54 : 04 SAN 54 : 62 : 20 LIM 62 : 70 : 05 SAN 70 : 81 : 20 LIM 81 : 173 : 04 SAN	O2 PVC 10 in. to urface 12 in ION MATERIAL: 0 INGS ARE: 0 S: Fro Fro S: Fro NITE 5 ft. to 25 of possible co LITHOL T IDY CLAY 31 CALI IDY CLAY IESTONE 04 SANDY	CASING 425 ft., Dia 1., weight 17 PVC 13 MILL SLOT 16 345 ft. to 16 0 ft. to 17 pt. to 18 25 ft. to 19 230 ft. to 19 10 pt. to 19 10 pt. to 19 10 pt. to 10	G JOINTS: 8LUED in. to 11 lbs/ft. 425 ft., From 0 ft., From 220 ft., From 425 ft., From 0 ft., From 220 ft. From 220 ft. From	O ft., Dia Wall thickness O ft. to O ft. to O ft. to O ft. to	in. to or gauge N Oft. Oft. Oft. Oft.	0 ft.	How many	

completed on (mo/day/year) 10/17/97 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 145
Under the business name of HENKLE DRILLING & SUPPLY

This Water Well Record was completed on (mo/day/yr) 10/29/97
Under the business name of HENKLE DRILLING & SUPPLY

This Water Well Record was completed on (mo/day/yr) 10/29/97

(Continued)						
	WATER WELL: Fraction 9 FORD SW 1/-			_	¦ Township Num ¦ T 26	ber ¦ Range Number S ¦ R 24 W
2 WATER WELL	OWNER: WINTER FEED dress, Box # : PO BOX 115	YARD INC.				ion of Water Resources
City, State	, IIP code : DODGE CITY,	KS 67801-011	15	Application	Number: 41,365	
191	218 : 31 CALICHE 234 : 19 SHALE 01 CLAY 269 : 01 CLAY 31 CALICHE 271 : 34 PYRITE 31 CALICHE 298 : 01 CLAY 327 : 19 SHALE 01 CLAY 336 : 19 SHALE 31 CALICHE 346 : 01 CLAY 19 SHALE	E		1		
347 ; 350 ; 357 ;	347 : 20 LIMESTONE 350 : 31 CALICHE 23 SANDS 357 : 23 SANDSTONE 31 CAL 422 : 23 SANDSTONE 31 CAL 430 : 19 SHALE	ICHE 19 SHALE		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
				, , , , , , , , , , , , , , , , , , ,		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1			; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;		
1 1 1 1 1 1 1 1 1 2 2				1 ! ! 1 1 1 1 1 1 1 1		
1 1 1 1 1 3 4 1				! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! ! !		
T I	• 1 1			* * * * * * * * * * * * * * * * * * *		