

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Ford

Location listed as:

Location changed to:

Section-Township-Range: None Given

31-26S-24W

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____

SW SW NE

Other changes: Initial statements: 120 MCCOUSTLAND #2

Changed to: 120 McCaustland Road 2

Comments: _____

verification method: well address, area road map, aerial photos on KGS website, and Fort Dodge 1:24,000 topo. map.

initials: DRL date: 3/6/2006

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726

to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: FORD 1/4 1/4 1/4 T S R E

Distance and direction from nearest town or city street address of well if located within city?
 120 MCCOUSTLAND #2 DODGE CITY, KS 67801-

2 WATER WELL OWNER: SMITH, CHAD Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 120 MCCOUSTLAND #2 Application Number:
 City, State, ZIP code: DODGE CITY, KS 67801-

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW W SE	NE E SE
---------------	---------------

4 DEPTH OF COMPLETED WELL 165 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 08/05/05
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm

Estimated Yield 80 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm

Bore Hole Diameter 10 in. to 165 ft., and in. to 0 ft.

WELL WATER TO BE USED AS: DOMESTIC

Was a chemical/bacteriological sample submitted to department? No;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED
 Blank casing diameter 5 in. to 165 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 21
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 120 ft. to 160 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

GRAVEL PACK INTERVALS: From 25 ft. to 60 ft., From 0 ft. to 0 ft.
 From 70 ft. to 165 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout Intervals: From 5 ft. to 25 ft., From 60 ft. to 70 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: NONE
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 05 CLAY 37 FIN-COAR SAN			
20	35	37 FIN-COAR SAN 38 SMAL-MED GRA			
35	80	32 TAN CLAY			
80	120	37 FIN-COAR SAN			
120	140	37 FIN-COAR SAN 06 SMALL GRAVEL			
140	160	37 FIN-COAR SAN 38 SMAL-MED GRA			
160	180	07 BLUE SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/08/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/22/05 under the business name of JOB'S WELL SERVICE, INC. by (signature) *Jared Cook*