COUNTY: FORD SW	ion 1/4 SW 1/4 NW 1/4	; 18	T 26	Number S	; Range I ; R 24	vumber ¥
Distance and direction from nearest 1 114 ROAD ON HIGHWAY 50 BYPASS - 3/4 I		f well if located	within city?			
WATER WELL OWNER: NIGHTENGA RR#, St. Address, Box # : NORTH STAN City, State, ZIP code : DODGE CIT	R ROUTE 10816 115 Rd		Agriculture, D	ivision of I	Water Res	ources
LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX:	4 DEPTH OF COMPLETED WELL Depth(s) Groundwater Enc			2. 0 f	t. 3.	0 f
NW NE	WELL'S STATIC WATER LEVEL Pump testdata:	82 ft. below 1 Well water was				
	Estimated Yield 45 gpm:					0 9
* ^ E	Bore Hole Diameter)5 ft., and	in. to	0 ft.	
SW	WELL WATER TO BE USED AS:			monto No .		1
	Was a chemical/bacteriolog If yes, mo/day/yr sample w				ell disinf	ected?
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE:	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT	to Oft., I s/ft. Wall thick	ness or gauge h		14	
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE:	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC	to Oft., I s/ft. Wall thicks ., From Oft, From Oft, From Oft.	to 0 ft. to 0 ft. to 0 ft.			
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possib	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT From 160 ft. to 200 ft. From 0 ft. to 0 ft. From 25 ft. to 205 ft. From 0 ft. to 0 ft.	to 0 ft., 1 s/ft. Wall thicks ., From 0 ft, From 0 ft, From 0 ft, From 0 ft.	to 0 ft.	0 ft.	How many	 feet?
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possib Direction from well? FROM ! TO ! ! O ! 20 01 TOPSOIL 05 CL 20 40 35 CALACHIE WHIT	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT From 160 ft. to 200 ft. From 0 ft. to 0 ft. From 25 ft. to 205 ft. From 0 ft. to 0 ft. 25 ft., From 0 ft. to 25 ft., From NONE ITHOLOGIC LOG AY 35 CALACHIE E 05 CLAY	to 0 ft., 1 s/ft. Wall thicks ., From 0 ft, From 0 ft, From 0 ft, From 0 ft.	to 0 ft.	0 ft.		
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possib Direction from well? FROM TO 1 0	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT From 160 ft. to 200 ft. From 0 ft. to 0 ft. From 25 ft. to 205 ft. From 0 ft. to 0 ft. 25 ft., From 0 ft. to ile contamination: NONE ITHOLOGIC LOG AY 35 CALACHIE E 05 CLAY FINE-MEDSAND 19 LAYERS CLAY 19 LAYERS CLAY LAYERS 35 CALACHIE	to Oft., I s/ft. Wall thicks ., From Oft, From Oft, From Oft, From Oft.	to 0 ft. on 0 ft.	0 ft.	How many	
GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possib Direction from well? FROM	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT From 160 ft. to 200 ft. From 0 ft. to 0 ft. From 25 ft. to 205 ft. From 0 ft. to 0 ft. 25 ft., From 0 ft. to Die contamination: NONE ITHOLOGIC LOG AY 35 CALACHIE E 05 CLAY FINE-MEDSAND 19 LAYERS CLAY 19 LAYERS CLAY LAYERS CLAY LAYERS	to Oft., I s/ft. Wall thicks ., From Oft, From Oft, From Oft, From Oft.	to 0 ft. on 0 ft.	0 ft.	How many	
Blank casing diameter 5 in. Casing height above land surface TYPE OF SCREEN OR PERFORATION MATERI SCREEN OR PERFORATION OPENINGS ARE: SCREEN PERFORATED INTERVALS: GRAVEL PACK INTERVALS: GROUT MATERIAL BENTONITE Grout Intervals: From 5 ft. to What is the nearest source of possib Direction from well? FROM	to 205 ft., Dia in. 12 in., weight 200 lbs AL: PVC SAW CUT From 160 ft. to 200 ft. From 0 ft. to 0 ft. From 25 ft. to 205 ft. From 0 ft. to 0 ft. 25 ft., From 0 ft. to Die contamination: NONE ITHOLOGIC LOG AY 35 CALACHIE E 05 CLAY FINE-MEDSAND 19 LAYERS CLAY 19 LAYERS CLAY LAYERS CLAY LAYERS	to Oft., I s/ft. Wall thicks ., From Oft, From Oft, From Oft, From Oft.	to 0 ft. on 0 ft.	0 ft.	How many	