WATER WELL RECORD	Form WWC-5	Division of Wate	er Resources App. No	3.	
1 LOCATION OF WATER WELL:	Fraction  1/4 VE 1/4 SE 1/4 SE 1/4  if unknown distance & direction	Section Number		Range Number	
County: Ford Street/Rural Address of Well Location;	if unknown distance & direction	Global Positioning	T 26 S System (GPS) in	R 24 DE W	
from nearest town or intersection: If at		Latitude:		(in decimal degrees)	
			Longitude: (in decimal degrees) Elevation:		
		Datum: WGS 8	4, □ NAD 83, □	NAD 27	
2 WATER WELL OWNER: Marin Such ne		Collection Method:			
2 WATER WELL OWNER: Paris Such ne RR#, Street Address, Box #: 11 705 US Hwy 50 City, State, ZIP Code : Wright, K567882		☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
wrig	14116767882	Est. Accuracy:			
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	$\Im$			
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.					
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
Pump test data: Well water was ft. after hours pumping gpm EST. YIELD YELD gpm Well water was ft. after hours pumping gpm					
W					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)  Irrigation Industrial Domestic-lawn & garden Monitoring well					
Was a chemical/bacteriological sample submitted to Department?  Yes No					
S If yes, mo/day/yr sample was submitted					
water wer distincted? A res 100					
5 TYPE OF CASING USED: Steel PVC Other Other					
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface. A ft., weight lbs./ft., Wall thickness or gauge No. #200.					
Casing height above land surface					
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)					
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)					
Louvered shutter  Key punched  Sew cut, Souther (specify)  SCREEN-PERFORATED INTERVALS: From					
From					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From5 ft. to25 ft., From ft. to ft., From ft., From ft. to ft. what is the nearest source of possible contamination:					
Septic tank    Septic tank					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well					
Direction from well	Distance			6 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	
FROM TO LITHOLOG				GGING INTERVALS	
2 Topsoil 2 15 tan clay 15 20 Caliche	183	187 Red	Clay	The second secon	
2 15 tan Clay					
20 60 Tan Elay & L	impstone,				
60 70 white Clay	& Cimestone				
	Bando Clau				
110 36 4 llow South	Clase				
176 183 Brown & Yello	w Clay w/				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was A constructed, a reconstructed, or plugged					
under my jurisdiction and was completed on (mo/day/year)					
Kansas Water Well Contractor's License No 1899. This Water Well Record was completed on (mo/day/year) 1999.					
under the business name of So with west					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212					