


1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ S1/2 $\frac{1}{4}$ SW $\frac{1}{4}$ Section Number 20 Township Number T 26 S Range Number R 24 EW

Distance and direction from nearest town or city street address of well if located within city?
 2 Miles North of Dodge City

2 WATER WELL OWNER: Ford County Landfill
 RR#, St. Address, Box #: Jetmore Star Route Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Dodge City, Ks. 67801 #10S Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 150 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 132.01 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 8 in. to 150 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter: 4 in. to 130 ft. Dia. in. to ft. Dia. in. to ft.
 Casing height above land surface: 30 in. weight 2.071 lbs./ft. Wall thickness or gauge No. 237
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 130 ft. to 150 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 125 ft. to 150 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 119 ft., From 119 ft. to 125 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Landfill
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Surface	129	140	Sandy Clay & Caliche Strks.
3	9	Loess	140	150	Silty Fine Sand w/some Sand Strks.
9	47	Clay w/Caliche Strks.			
47	69.5	Caliche w/Clay Strks.			
69.5	71	Clay			
71	72	Caliche			
72	77.5	Med. Sand w/Clay & Caliche Str.			
77.5	80	Hard Caliche			
80	81.5	Med. Sand			
81.5	85	Sandy Clay, Caliche & a few Sand St.			
85	89	Med. Sand & Gravel			
89	113	Sandy Clay w/a Few Caliche St.			
113	124	Cemented Sand w/a Few Caliche St.			
124	129	Med. Sand & Gravel w/a Few Clay Str.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-15-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 554 This Water Well Record was completed on (mo/day/yr) 9-23-94 under the business name of Woofter Pump & Well, Inc. by (signature)