

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Ford		NE 1/4 SE 1/4 SW 1/4	27	T 26 S	R 25 E (M)
Distance and direction from nearest town or city street address of well if located within city? 2305 West Wyatt Earp, Dodge City, KS.					
2 WATER WELL OWNER: Byron Winans RR#, St. Address, Box #: P.O. Box 446 City, State, ZIP Code: Dodge City, Ks. 67801 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 34' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 36.22 ft. below land surface measured on mo/day/yr 11-12-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 45' ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No (X)			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X Blank casing diameter 2.375 in. to 32' ft. Dia in. to ft. Dia in. to SDR 13 ft. Casing height above land surface 2' in. weight lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From 45' ft. to 30' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 45' ft. to 28' ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 28' ft. to 4' ft. From 4' ft. to 0' ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northeast How many feet? 120'					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	2	Dk brn clay, dry, tight, no odor.			
2	6	Med brn clay, tight, no odor.			
6	12	Lt brn silty clay, dry, no odor.			
12	16	Dk brn silty clay w/ trace of fine sand, dry, fraible.			
16	19	Med brn silty clay, moist, no odor.			
19	23.5	Fine sand, dry, no odor.			
23.5	31	Fine-coarse grained sand, dry, no odor, well graded, subrounded.			
31	43.5	Med-coarse sand & gravel w/ few cobbles, well graded. moist - wet at 34', wet, no odor.			
43.5	45	Brn-tan brn silty clay, firm, moist to wet, no odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) Constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-12-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 11-16-96 under the business name of JB Environmental Drilling by (signature) James Baker					